

Package ‘ForeComp’

February 20, 2026

Type Package

Title Size-Power Tradeoff Visualization for Equal Predictive Ability of Two Forecasts

Version 1.0.0

Author Nathan Schor [aut],
Minchul Shin [aut, cre, cph]

Maintainer Minchul Shin <visiblehand@gmail.com>

Description Offers tools for visualizing and analyzing size and power properties of tests for equal predictive accuracy, including Diebold-Mariano and related procedures. Provides multiple Diebold-Mariano test implementations based on fixed-smoothing approaches, including fixed-b methods such as Kiefer and Vogelsang (2005) <[doi:10.1017/S0266466605050565](https://doi.org/10.1017/S0266466605050565)>, and applications to tests for equal predictive accuracy as in Coroneo and Iacone (2020) <[doi:10.1002/jae.2756](https://doi.org/10.1002/jae.2756)>, alongside conventional large-sample approximations. HAR inference involves nonparametric estimation of the long-run variance, and a key tuning parameter (the truncation parameter) trades off size and power. Lazarus, Lewis, and Stock (2021) <[doi:10.3982/ECTA15404](https://doi.org/10.3982/ECTA15404)> theoretically characterize the size-power frontier for the Gaussian multivariate location model. ‘ForeComp’ computes and visualizes the finite-sample size-power frontier of the Diebold-Mariano test based on fixed-b asymptotics together with the Bartlett kernel. To compute finite-sample size and power, it fits a best approximating ARMA process to the input data and reports how the truncation parameter performs and how robust testing outcomes are to its choice.

License GPL (>= 3)

Encoding UTF-8

URL <https://github.com/mcmcs/ForeComp>

BugReports <https://github.com/mcmcs/ForeComp/issues>

LazyData true

Depends R (>= 3.5.0), stats

Imports forecast, astsa, ggplot2, rlang

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

RoxygenNote 7.3.3

NeedsCompilation no

Repository CRAN

Date/Publication 2026-02-20 15:40:07 UTC

Contents

dm.test.bt	2
dm.test.bt.fb	3
dm.test.cnr.t	4
dm.test.cnr.w	4
dm.test.ewc.fb	5
dm.test.im	6
dm.test.r	6
dm.test.r.m	7
dm.test.wpe.fb	8
loss.diff.p	9
mikedata	10
PGDP	11
Plot_Tradeoff	11
RGDP	13
TBILL	14
UNEMP	14

Index **15**

dm.test.bt	<i>Diebold-Mariano Test (Bartlett kernel, normal approximation)</i>
------------	---

Description

Diebold-Mariano Test (Bartlett kernel, normal approximation). This is a two-sided test.

Usage

```
dm.test.bt(d, M = NA, Mopt = NA, cl = 0.05)
```

Arguments

d	loss differential
M	truncation parameter for the Bartlett kernel (if M = NA, then Mopt = 2 by default)
Mopt	option for automatic bandwidth, 1 if Lazarus et al. (2018), 2 if Newey and West (1994, default), 3 if Andrews textbook NW ($M = \lceil 0.75T^{1/3} \rceil$), 4 if CI baseline ($M = \lfloor T^{1/2} \rfloor$)
cl	confidence level (default = 0.05, i.e., 5%)

Value

This function returns a class with the following elements

- `rej` is a T/F value. TRUE (reject), FALSE (accept)
- `stat` is a test statistic
- `pval` is an associated p-value

Author(s)

Minchul Shin

dm.test.bt.fb

Diebold-Mariano Test (Bartlett kernel, fixed-b approximation)

Description

Diebold-Mariano Test (Bartlett kernel, fixed-b approximation). This is a two-sided test.

Usage

```
dm.test.bt.fb(d, M = NA, Mopt = NA, cl = 0.05)
```

Arguments

<code>d</code>	loss differential
<code>M</code>	truncation parameter for the Bartlett kernel (if <code>M = NA</code> , then <code>Mopt = 1</code> by default)
<code>Mopt</code>	option for automatic bandwidth, 1 if Lazarus et al. (2018, default), 2 if Newey and West (1994), 3 if Andrews textbook NW ($M = \lceil 0.75T^{1/3} \rceil$), 4 if CI baseline ($M = \lfloor T^{1/2} \rfloor$)
<code>cl</code>	confidence level (default = 0.05, i.e., 5%), Only 0.05 (5%) or 0.10 (10%) are allowed.

Value

This function returns a class with the following elements

- `rej` is a T/F value. TRUE (reject), FALSE (accept)
- `stat` is a test statistic

Author(s)

Minchul Shin

dm.test.cnr.t	<i>CNR (2017), ltl-test statistic</i>
---------------	---------------------------------------

Description

Randomization test based on asymptotic symmetry, ltl-test statistic

Usage

```
dm.test.cnr.t(d, q = 2, cl = 0.05)
```

Arguments

d	loss differential
q	number of blocks
cl	confidence level (default = 0.05, i.e., 5%)

Value

This function returns a class with the following elements

- rej is a T/F value. TRUE (reject), FALSE (accept)
- stat is a test statistic
- pval is an associated p-value

Author(s)

Minchul Shin

dm.test.cnr.w	<i>CNR (2017), Wald-statistic</i>
---------------	-----------------------------------

Description

Randomization test based on asymptotic symmetry, Wald-statistic

Usage

```
dm.test.cnr.w(d, q = 2, cl = 0.05)
```

Arguments

d	loss differential
q	number of blocks
cl	confidence level (default = 0.05, i.e., 5%)

Value

This function returns a class with the following elements

- `rej` is a T/F value. TRUE (reject), FALSE (accept)
- `stat` is a test statistic
- `pval` is an associated p-value

Author(s)

Minchul Shin

dm.test.ewc.fb	<i>Diebold-Mariano Test (EWC, fixed-b approximation)</i>
----------------	--

Description

Diebold-Mariano Test (EWC, fixed-b approximation). This is a two-sided test.

Usage

```
dm.test.ewc.fb(d, B = NA, Bopt = NA, cl = 0.05)
```

Arguments

<code>d</code>	loss differential
<code>B</code>	truncation parameter for the EWC long-run variance estimator (if <code>B = NA</code> , then <code>Bopt = 1</code> by default)
<code>Bopt</code>	option for automatic bandwidth, 1 if Lazarus et al. (2018, default, $B = \lfloor 0.4T^{2/3} \rfloor$)
<code>cl</code>	confidence level (default = 0.05, i.e., 5%)

Value

This function returns a class with the following elements

- `rej` is a T/F value. TRUE (reject), FALSE (accept)
- `stat` is a test statistic
- `pval` is an associated p-value

Author(s)

Minchul Shin

dm.test.im

Ibragimov and Muller (2010)

Description

t-Statistic based HAR-inference by Ibragimov and Muller (2010).

Usage

```
dm.test.im(d, q = 2, cl = 0.05)
```

Arguments

d	loss differential
q	number of blocks. When <code>length(d)</code> is not divisible by <code>q</code> , this implementation uses near-equal nonoverlapping blocks (block sizes differ by at most one) and issues a warning.
cl	confidence level (default = 0.05, i.e., 5%)

Value

This function returns a class with the following elements

- `rej` is a T/F value. TRUE (reject), FALSE (accept)
- `stat` is a test statistic
- `pval` is an associated p-value

Author(s)

Minchul Shin

dm.test.r

Diebold-Mariano Test (with an original recommendation)

Description

This function performs the Diebold-Mariano test with their original recommendation. Let d_t be a sequence of loss differential, $t = 1, 2, \dots, T$. Then, the function performs a statistical test for the following null hypothesis:

$$E[d_t] = 0$$

This function follows the original recommendation by Diebold and Mariano (1995), where the long-run variance is estimated using the rectangular kernel truncated at $(h - 1)$. This function performs a two-sided test. Normal approximation is used to calculate critical values.

Usage

```
dm.test.r(d, h = 1, cl = 0.05)
```

Arguments

d	loss differential
h	h-step-ahead forecast (default = 1, i.e., comparing one-step-ahead forecasts)
cl	confidence level (default = 0.05, i.e., 5%)

Value

This function returns a class with the following elements

- `rej` is a T/F value. TRUE (reject), FALSE (accept)
- `stat` is a test statistic
- `pval` is an associated p-value

Author(s)

Minchul Shin

dm.test.r.m

Diebold-Mariano Test (Modified-DM)

Description

Diebold-Mariano Test (Modified-DM). Finite-sample modification to the original DM's test. This is a two-sided test.

Usage

```
dm.test.r.m(d, h = 1, cl = 0.05)
```

Arguments

d	loss differential
h	h-step-ahead forecast (default = 1, i.e., one-step-ahead forecasts)
cl	confidence level (default = 0.05, i.e., 5%)

Details

This function is based on [dm.test](#) in the "forecast" package on CRAN.

Value

This function returns a class with the following elements

- `rej` is a T/F value. TRUE (reject), FALSE (accept)
- `stat` is a test statistic
- `pval` is an associated p-value

Author(s)

Minchul Shin

<code>dm.test.wpe.fb</code>	<i>Diebold-Mariano Test (WPE, fixed-m approximation)</i>
-----------------------------	--

Description

Diebold-Mariano Test (WPE, fixed-m approximation). This is a two-sided test. See Coroneo and Iacone (2020)

Usage

```
dm.test.wpe.fb(d, M = NA, Mopt = NA, cl = 0.05)
```

Arguments

<code>d</code>	loss differential
<code>M</code>	truncation parameter for the WPE long-run variance estimator (if <code>M = NA</code> , then <code>Mopt = 1</code> by default)
<code>Mopt</code>	option for automatic bandwidth, 1 if Coroneo and Iacone's default value ($M = \text{floor}(T^{1/3})$)
<code>cl</code>	confidence level (default = 0.05, i.e., 5%)

Value

This function returns a class with the following elements

- `rej` is a T/F value. TRUE (reject), FALSE (accept)
- `stat` is a test statistic
- `pval` is an associated p-value

Author(s)

Minchul Shin

loss.diff.p

*Loss differential from two point forecasts***Description**

This function computes the loss differential from two point forecasts. Let $f_{1,t}$ and $f_{2,t}$ be point forecasts generated by the forecaster 1 (e.g., forecasting model 1) and the forecaster 2 (e.g., forecasting model 2), respectively. y_t is a forecasting target that both $f_{1,t}$ and $f_{2,t}$ try to forecast. For a given loss function the loss differential is defined and computed as

$$d_t = L(y_t, f_{1,t}) - L(y_t, f_{2,t})$$

for $t = 1, 2, \dots, T$.

Usage

```
loss.diff.p(y, f1, f2, type = "quad", ...)
```

Arguments

y	actual value, y_t , for $t = 1, 2, \dots, T$.
f1	point forecast 1, $f_{1,t}$, for $t = 1, 2, \dots, T$.
f2	point forecast 2, $f_{2,t}$, for $t = 1, 2, \dots, T$.
type	Type of loss functions to compare. <ul style="list-style-type: none"> • "quad" : quadratic loss function (default) • "abs" : absolute loss function • "check" : check (quantile) loss function • "linex" : linex loss function
...	Extra parameters to compute loss function. <ul style="list-style-type: none"> • For type="quad" : no extra parameter is needed. • For type="abs" : no extra parameter is needed. • For type="check" : a scalar parameter (tau) is needed. $\tau \in [0, 1]$. Default value is tau=0.5 if unspecified. • For type="linex" : a scalar parameter (c) is needed. c is a real number. Default value is c=1.

Details

Type of loss functions. Define $e_t = y_t - f_t$. Quadratic loss function is defined as

$$L(y_t, f_t) = e_t^2$$

Absolute loss function is defined as

$$L(y_t, f_t) = |e_t|$$

Check loss function is defined as

$$L(y_t, f_t) = (\tau - 1(e_t < 0))e_t$$

Linex loss function is defined as

$$L(y_t, f_t) = \exp(ce_t) - ce_t - 1$$

If c is positive (negative) real number, then the linex function is exponential (linear) for $e > 0$ and linear (exponential) for $e < 0$.

A sample average of the returned sequence, $\bar{d}_t = \frac{1}{T} \sum_{t=1}^T d_t$, is the difference in average loss from forecaster 1 and forecaster 2. Positive \bar{d}_t means that the forecaster 2 incurs lower expected loss compared to the forecaster 1. Negative \bar{d}_t means that the forecaster 1 incurs lower expected loss compared to the forecaster 2. Statistical testing to test whether the loss differential is zero in expectation is possible. See, for example, [dm.test.r](#).

Value

This function returns a sequence of the loss differential, d_t .

Author(s)

Minchul Shin

mikedata

Simulated data 1

Description

A dataset containing y , $f1$, $f2$ based on one of McCracken (2019)'s data generating processes. The name of the specification is "Unconditional-Rolling". $R = 175$, $Rbar = 175$, $h = 12$, $P = 75$; Note that the DGP is constructed in a way that there is no difference between $f1$ and $f2$ in terms of expected quadratic loss.

Usage

```
mikedata
```

Format

A data frame with 75 rows and 3 variables:

y Forecast target

f1 Point forecast based on forecasting model 1

f2 Point forecast based on forecasting model 2

Source

Simulated data.

PGDP	<i>Price Index for Gross National Product/Gross Domestic Product (PGDP)</i>
------	---

Description

Error Statistics for the Survey of Professional Forecasters for GNP/GDP Price Index

Usage

PGDP

Format

‘PGDP’ A data frame with 219 rows and 31 columns

Source

<https://www.philadelphiafed.org/-/media/frbp/assets/surveys-and-data/survey-of-professional-forecasters/data-files/pgdp/data_spf_error_statistics_pgdp_3_aic.xls?la=en&hash=148987D03D54DA5391A44F28CBC12729>

Plot_Tradeoff	<i>Visualizes the size distortion maximum power loss tradeoff from the Diebold-Mariano test for equal predictive accuracy</i>
---------------	---

Description

‘Plot_Tradeoff’ creates a plot to show sensitivity of statistical significance to the choice of bandwidth and how size distortion and maximum power loss vary. It is designed for the Diebold-Mariano test for equal predictive accuracy (Diebold and Mariano, 1995). For a size-power tradeoff plot, see Lazarus, Lewis, Stock, and Watson (2018) and Lazarus, Lewis, and Stock (2021).

Usage

```
Plot_Tradeoff(
  data,
  f1 = NULL,
  f2 = NULL,
  y = NULL,
  loss_function = NULL,
  n_sim = 1000,
  m_set = NULL,
  cl = 0.05,
  verbose = TRUE,
  no_m_label = FALSE,
  na_handling = c("zero", "drop", "error")
)
```

Arguments

data	A data frame.
f1	Column containing forecaster 1's predictions. Should be a string.
f2	Column containing forecaster 2's predictions. Should be a string.
y	Column containing the realized value for the outcome variable. Should be a string.
loss_function	The transformation applied to the forecast error. Defaults to squared error loss. The user supplied function should take two inputs and a scalar output, $\text{loss} = \text{loss_function}(f, y)$. For example, quadratic loss function would be defined as $\text{loss_function} = \text{function}(f, y)\{(f-y)^2\}$.
n_sim	The number of simulations used to generate the ARIMA model. Defaults to 1,000.
m_set	The truncation parameter. If NULL, the function constructs a default grid centered around the package default bandwidth for <code>dm.test.bt.fb</code> , $M_0 = \lceil 1.3\sqrt{T} \rceil$ (LLSW), where T is the effective sample size after applying <code>na_handling</code> . It should be a vector of integers with the values of M you would like to plot.
cl	Significance level used in the hypothesis test. Defaults to 0.05. Only 0.05 and 0.10 are currently supported because the fixed-b approximation is implemented for these levels.
verbose	TRUE to print out the progress to the console. Defaults to TRUE.
no_m_label	TRUE to plot without m labels. Defaults to FALSE.
na_handling	How to handle missing/non-finite loss differentials. "zero" (default) replaces them with 0 (Application 2 convention), "drop" removes them (Application 1 convention), and "error" stops if any are present.

Value

A list of length 2. The first element is a `ggplot2` object of the size-power tradeoff. The second element is the underlying data used to construct the plot in element 1.

Author(s)

Nathan Schor and Minchul Shin

References

- Diebold, F. X. & Mariano, R. S. (1995), Comparing Predictive Accuracy, *Journal of Business & Economic Statistics*, **13**(3), 253-263.
- Lazarus, E., Lewis, D. J., Stock, J. H. & Watson, M. W. (2018), HAR Inference: Recommendations for Practice, *Journal of Business & Economic Statistics*, **36**(4), 541-559.
- Lazarus, E., Lewis, D. J. & Stock, J. H. (2021), The Size-Power Tradeoff in HAR Inference, *Econometrica*, **89**(5), 2497-2516.

Examples

```

# A typical example
set.seed(1234)
output = Plot_Tradeoff(
  data = TBILL,
  f1 = "SPFfor_Step1",
  f2 = "NCfor_Step1",
  y = "Realiz1",
  m_set = seq(from = 1, to = 70, by = 10)
)
output[[1]] # The first element is a ggplot2 object of the size-power tradeoff.
output[[2]] # The second element is the underlying data used to construct the plot in element 1.

# An example with a user supplied loss function
# To use the mean absolute error as a loss function rather than a quadratic loss function
set.seed(1234)
output = Plot_Tradeoff(
  data = TBILL,
  f1 = "SPFfor_Step1",
  f2 = "NCfor_Step1",
  y = "Realiz1",
  loss_function = function(f,y){ abs(f-y) },
  m_set = seq(from = 1, to = 50, by = 10)
)

# An example without (f1, f2, y). The function will take the first three columns and use them
set.seed(1234)
tmpdata = TBILL[, c("SPFfor_Step1", "NCfor_Step1", "Realiz1")] # data with [f1, f2, y]
Plot_Tradeoff(
  data = tmpdata,
  m_set = seq(from = 1, to = 50, by = 10)
)

```

 RGDP

Real Gross National Product/Gross Domestic Product (RGDP)

Description

Error Statistics for the Survey of Professional Forecasters for Real GNP/GDP

Usage

RGDP

Format

‘RDGP’ A data frame with 219 rows and 31 columns

Source

<https://www.philadelphiafed.org/-/media/frbp/assets/surveys-and-data/survey-of-professional-forecasters/data-files/rgdp/data_spf_error_statistics_rgdp_3_aic.xls?la=en&hash=3AC9E2D8A5299F93CA7E16CFAA974C22>

 TBILL

3-Month Treasury Bill Rate (TBILL)

Description

Error Statistics for the Survey of Professional Forecasters for Treasury Bill Rate (Three Month)

Usage

TBILL

Format

‘TBILL’ A data frame with 219 rows and 31 columns

Source

<https://www.philadelphiafed.org/-/media/frbp/assets/surveys-and-data/survey-of-professional-forecasters/data-files/tbill/data_spf_error_statistics_tbill_1_aic.xls?la=en&hash=F432350F84B0E4CCE9A1E9D399447CA9>

 UNEMP

Civilian Unemployment Rate (UNEMP)

Description

Error Statistics for the Survey of Professional Forecasters for Unemployment Rate

Usage

UNEMP

Format

‘UNEMP’ A data frame with 219 rows and 31 columns

Source

<https://www.philadelphiafed.org/-/media/frbp/assets/surveys-and-data/survey-of-professional-forecasters/data-files/unemp/data_spf_error_statistics_unemp_1_aic.xls?la=en&hash=4CAD0B11FEAB6C4D0F30C38965FE3354>

Index

* datasets

- mikedata, [10](#)
- PGDP, [11](#)
- RGDP, [13](#)
- TBILL, [14](#)
- UNEMP, [14](#)

- dm.test, [7](#)
- dm.test.bt, [2](#)
- dm.test.bt.fb, [3](#)
- dm.test.cnr.t, [4](#)
- dm.test.cnr.w, [4](#)
- dm.test.ewc.fb, [5](#)
- dm.test.im, [6](#)
- dm.test.r, [6](#), [10](#)
- dm.test.r.m, [7](#)
- dm.test.wpe.fb, [8](#)

- loss.diff.p, [9](#)

- mikedata, [10](#)

- PGDP, [11](#)
- Plot_Tradeoff, [11](#)

- RGDP, [13](#)

- TBILL, [14](#)

- UNEMP, [14](#)