

Package ‘GREENeR’

February 11, 2026

Type Package

Title Geospatial Regression Equation for European Nutrient Losses (GREEN)

Version 1.0.1

Author A. Udias [aut],
B. Grizzetti [aut],
O. Vigiak [aut],
J. Gomez [aut],
C. Alfaro [aut, cre],
A. Aloe [aut]

Maintainer C. Alfaro <c.alfarog@gmail.com>

Description Tools and methods to apply the model Geospatial Regression Equation for European Nutrient losses (GREEN);
Grizzetti et al. (2005) <[doi:10.1016/j.jhydrol.2004.07.036](https://doi.org/10.1016/j.jhydrol.2004.07.036)>;
Grizzetti et al. (2008);
Grizzetti et al. (2012) <[doi:10.1111/j.1365-2486.2011.02576.x](https://doi.org/10.1111/j.1365-2486.2011.02576.x)>;
Grizzetti et al. (2021) <[doi:10.1016/j.gloenvcha.2021.102281](https://doi.org/10.1016/j.gloenvcha.2021.102281)>.

License GPL-3

Encoding UTF-8

LazyData true

Imports FME (>= 1.3.6.1), data.table (>= 1.13.6), reshape2 (>= 1.4.4), ggplot2 (>= 3.3.5), graphics (>= 3.6.1), sf (>= 1.0-2), dplyr (>= 1.0.7), magrittr (>= 2.0.1), tmap (>= 3.3-2), gridExtra (>= 2.3), classInt (>= 0.4-3), grDevices (>= 3.5), networkD3 (>= 0.4), parallelly (>= 1.30.0)

Depends R (>= 3.5.0)

RoxygenNote 7.3.1

URL <https://github.com/calfarog/GREENeR>,
<https://calfarog.github.io/GREENeR/>

BugReports <https://github.com/calfarog/GREENeR/issues>

Suggests knitr, rmarkdown, codetools

VignetteBuilder knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2026-02-11 22:40:02 UTC

Contents

| | |
|---------------------------------|-----------|
| annual_data_TN | 2 |
| annual_data_TP | 3 |
| calib_boxplot | 4 |
| calib_dot | 5 |
| calib_green | 6 |
| catch_data_TN | 7 |
| catch_data_TP | 7 |
| compare_calib | 8 |
| green_shares | 9 |
| input_maps | 10 |
| input_plot | 11 |
| input_Tserie | 12 |
| input_Tserie_area | 13 |
| LakeRetent_plot | 14 |
| N4_sankey | 14 |
| nutrient_maps | 15 |
| nutrient_tserie | 16 |
| nutrient_tserie_darea | 17 |
| read_geometry | 18 |
| read_NSdata | 19 |
| references_plot | 20 |
| region_nut_balance | 20 |
| scatter_plot | 21 |
| select_params | 22 |
| shreve | 23 |
| simobs_annual_plot | 24 |
| Index | 25 |

| | |
|----------------|-----------------------|
| annual_data_TN | <i>Annual data TN</i> |
|----------------|-----------------------|

Description

Defines the sources of nutrient (nitrogen) for each year and catchments.

Usage

annual_data_TN

Format

A data frame with 14 variables:

BasinID integer. The basin unique identifier.

YearValue integer. The year for which data are defined.

HydroID integer positive. Unique catchment identifier.

NextDownID integer. Unique identifier of the catchment to which the catchment goes.

Atm double. Annual nitrogen deposition from atmosphere (ton/yr).

Min double. Annual amount of nitrogen from mineral fertilisers (ton/yr).

Man double. Annual amount of nitrogen in manure fertilisers (ton/yr).

Fix double. Annual amount of nitrogen fixation by leguminous crops and fodder (ton/yr).

Soil double. Annual amount of nitrogen fixation by bacteria in soils (ton/yr).

Sd double. Nitrogen input from scattered dwellings (ton/yr).

Ps double. Nitrogen input from point sources (ton/yr).

YearlyMass double. Observed annual total nitrogen load (TN ton/yr) from monitoring station data.

ForestFraction double. Non-agricultural land cover in the catchment (fraction).

InvNrmRain double. Inverse of normalized rainfall.

annual_data_TP

Annual data TP

Description

Defines the sources of nutrient (phosphorus) for each year and catchments.

Usage

annual_data_TP

Format

A data frame with 12 variables:

BasinID integer. The basin unique identifier.

YearValue integer. The year for which data are defined.

HydroID integer positive. Unique catchment identifier.

NextDownID integer. Unique identifier of the catchment to which the catchment goes.

Bg double. Annual amount of phosphorus background losses (ton/yr).

Min double. Annual amount of phosphorus mineral fertilisers (ton/yr).

Man double. Annual amount of phosphorus in manure fertilisers (ton/yr).

Sd double. Phosphorus input from scattered dwellings (ton/yr).

Ps double. Phosphorus input from point sources (ton/yr).
 YearlyMass double. Observed annual total phosphorus load (TP ton/yr) from monitoring station data.
 ForestFraction double. Non-agricultural land cover in the catchment (fraction).
 InvNrmRain double. Inverse of normalized rainfall.

calib_boxplot *Boxplot of best parameters*

Description

Returns boxplots of best model parameters ranked according to different goodness-of-fit measures, and also boxplot with the distribution of the parameters values.

Usage

```
calib_boxplot(df_cb, rate_bs)
```

Arguments

df_cb data frame. Table with the result of the calibration process.
 rate_bs numeric. Rate (%) of parameters selected from the whole set produced in the calibration.

Value

Multiple boxplots

Examples

```
# the data of the TN scenario
data(catch_data_TP)
data(annual_data_TP)
# the parameter for the calibration of the model
n_iter <- 2 # number of iterations
# the lower limits for all params (alpha_P, alpha_L, sd_coef)
low <- c(10, 0.000, 0.1)
# the upper limits for all params (alpha_P, alpha_L, sd_coef)
upp <- c(70, 0.3, 0.9)
# years in which the model should be executed
years <- 1990:2018
# execution of the calibration
df_calib <- calib_green(catch_data_TP, annual_data_TP, n_iter, low, upp,
years)
# Generating the box plots
rateBS <- 5 # rate of best set of parameter to include in the plots
calib_boxplot(df_calib, rateBS)
```

`calib_dot`*Dot plot of goodness-of-fit metric vs parameter value*

Description

Dot plot of goodness-of-fit metric vs parameters value

Usage

```
calib_dot(df_cb, param)
```

Arguments

| | |
|--------------------|---|
| <code>df_cb</code> | data frame. A table with the result of the calibration process. |
| <code>param</code> | character. Goodness of fit measures. See alternatives link "NSE" "rNSE", "NSE", "mNSE", "MAE", "PBIAS", "cp", "R2". |

Value

Multiple dot plots

Examples

```
# the data of the TN scenario
data(catch_data_TN)
data(annual_data_TN)
# the parameter for the calibration of the model
n_iter <- 2 # number of iterations
# the lower limits for all params (alpha_P, alpha_L, sd_coef)
low <- c(10, 0.000, 0.1)
# the upper limits for all params (alpha_P, alpha_L, sd_coef)
upp <- c(70, 0.3, 0.9)
# years in which the model should be executed
years <- 1990:2018
# execution of the calibration
df_calib <- calib_green(catch_data_TN, annual_data_TN, n_iter, low, upp,
years)
# Generating the dot plots
gof_mes <- "NSE"
calib_dot(df_calib, gof_mes)
```

`calib_green`*Calibration of the GREEN model*

Description

Runs GREEN model calibration

Usage

```
calib_green(catch_data, annual_data, n_iter, low, upp, years)
```

Arguments

| | |
|--------------------------|---|
| <code>catch_data</code> | data frame. Definition of the topological sequence of catchments. |
| <code>annual_data</code> | data frame. Sources of nutrient for each year and catchments. |
| <code>n_iter</code> | numeric. Number of iterations for the calibration process. |
| <code>low</code> | numeric. Lower bounds of the calibration parameters. |
| <code>upp</code> | numeric. Upper bounds of the calibration parameters. |
| <code>years</code> | integer. Years to be used in the calibration. For sequences use <code>c(yearini:yearend)</code> . |

Value

One object, a data frame with the model calibration

Examples

```
# the data of the TN scenario
data(catch_data_TN)
data(annual_data_TN)
# the parameter for the calibration of the model
n_iter <- 2 # number of iterations
# the lower limits for all params (alpha_P, alpha_L, sd_coef)
low <- c(10, 0.000, 0.1)
# the upper limits for all params (alpha_P, alpha_L, sd_coef)
upp <- c(70, 0.3, 0.9)
# years in which the model should be executed
years <- 1990:2018
# execution of the calibration
dF_calib <- calib_green(catch_data_TN, annual_data_TN, n_iter, low, upp,
years)
```

| | |
|---------------|----------------------|
| catch_data_TN | <i>Catch data TN</i> |
|---------------|----------------------|

Description

Defines the topological sequence of catchments for nitrogen.

Usage

catch_data_TN

Format

A data frame with 5 variables:

HydroID integer positive. Unique catchment identifier.

To_catch integer. Unique identifier of the catchment to which the catchment goes. Note that for the outlet To_catch== -1.

Shreve integer. this indicates the Shreve order of the topological sequence in the stream network.

LakeFrRet fraction, 0-1. Lake retention fraction.

NrmLengthKm double. Normalized length of catchment reach.

| | |
|---------------|----------------------|
| catch_data_TP | <i>Catch data TP</i> |
|---------------|----------------------|

Description

Defines the topological sequence of catchments for phosphorus.

Usage

catch_data_TP

Format

A data frame with 5 variables:

HydroID integer positive. Unique catchment identifier.

To_catch integer. Unique identifier of the catchment to which the catchment goes. Note that for the outlet To_catch== -1.

Shreve integer. this indicates the Shreve order of the topological sequence in the stream network.

LakeFrRet fraction, 0-1. Lake retention fraction.

NrmLengthKm double. Normalized length of catchment reach.

 compare_calib

Plot comparing observed vs modeled loads for two set of parameters

Description

Returns a scatter plot comparing observed versus modeled loads obtained with two model parameter sets

Usage

```
compare_calib(
  catch_data,
  annual_data,
  alpha_p1,
  alpha_l1,
  sd_coef1,
  alpha_p2,
  alpha_l2,
  sd_coef2,
  years,
  name_basin,
  setPlabels
)
```

Arguments

| | |
|-------------|--|
| catch_data | data frame. Definition of the topological sequence of catchments. |
| annual_data | data frame. Sources of nutrient for each year and catchments. |
| alpha_p1 | numeric. The basin retention coefficient of the first set of parameters. |
| alpha_l1 | numeric. The river retention coefficient of the first set of parameters. |
| sd_coef1 | numeric. Fraction of domestic diffuse sources that reaches the stream network of the first set of parameters. |
| alpha_p2 | numeric. The basin retention coefficient of the second set of parameters. |
| alpha_l2 | numeric. The river retention coefficient of the second set of parameters. |
| sd_coef2 | numeric. Fraction of domestic diffuse sources that reaches the stream network of the second set of parameters. |
| years | numeric. Years to be shown in the plot. |
| name_basin | character. Name of the basin (title of the plot). |
| setPlabels | character. Labels identifying each set of parameter. |

Value

A scatter plot and a list with two data frames with model GREEN applied to two model parameter sets

Examples

```

# the data of the TN scenario
data(catch_data_TN)
data(annual_data_TN)

# the first set of parameters to assess the basin model
alpha_p <- 35.09
alpha_l <- 0.02
sd_coef <- 0.2

# the second set of parameters to assess the basin model
alpha_p2 <- 41.23
alpha_l2 <- 0.0015
sd_coef2 <- 0.6

# years in which the plot will we shown
years <- 1990:2018

nameBasin <- "Lay"

# generating the scatter plot comparing two set of parameters observed
# versus modeled loads by year
setPLabels <- c("bestNSE", "bestR2")
compare_calib(catch_data_TN, annual_data_TN, alpha_p , alpha_l, sd_coef,
alpha_p2, alpha_l2, sd_coef2, years, nameBasin, setPLabels)

```

green_shares

Geospatial Regression Equation parallel execution returning the source apportionment

Description

Run GREEN model with selected parameter set and returns the nutrient load by each source for all catchments in the Basin.

Usage

```
green_shares(catch_data, annual_data, alpha_p, alpha_l, sd_coef, loc_years)
```

Arguments

| | |
|-------------|---|
| catch_data | data frame. Definition of the topological sequence of catchments. |
| annual_data | data frame. Sources of nutrient for each year and catchments. |
| alpha_p | numeric. First model parameter, the basin retention coefficient. |
| alpha_l | numeric. Second model parameter, the river retention coefficient. |

sd_coef numeric. Third model parameter, fraction of domestic diffuse sources that reaches the stream network.

loc_years integer. Years in which the model should be executed.

Value

One object, a data frame with the nutrient load by each source for all catchments in the Basin

Examples

```
# the data of the TN scenario
data(catch_data_TN)
data(annual_data_TN)
# the parameter to assess the basin model
alpha_p <- 35.09
alpha_l <- 0.02
sd_coef <- 0.2
# year in which the model should be executed
loc_years <- 1990:2018
# Computing the source apportionment
basin_loads_s <- green_shares(catch_data_TN, annual_data_TN, alpha_p, alpha_l,
sd_coef, loc_years)
```

input_maps

Map average load input by source

Description

Map showing the mean load input by source

Usage

```
input_maps(
  catch_data,
  annual_data,
  sh_file,
  plot.type,
  style_map = "fisher",
  scale_barTextS = 0.7,
  legend_position = 1
)
```

Arguments

| | |
|-----------------|--|
| catch_data | data frame. Definition of the topological sequence of catchments. |
| annual_data | data frame. Sources of nutrient for each year and catchments. |
| sh_file | sf object. The spatial information. |
| plot.type | character. Alternatives of the map: input load (kt) by type divided by year and catchment. "gr1": by km2; "gr2": by year/km2. |
| style_map | character. Alternatives to create the intervals in the maps. Chosen style: one of "fixed", "sd", "equal", "pretty", "quantile", "kmeans", "hclust", "bclust", "fisher", "jenks". |
| scale_barTextS | numeric. To modify the size of the text in the legend. |
| legend_position | numeric. Legend position: 1 (default): "right", "bottom"; 2: "left", "up"; 3: "right", "bottom"; 4: "right", "up". |

Value

No return value, called for the side effect of drawing a plot

Examples

```
# the data of the TN scenario
data(catch_data_TN)
data(annual_data_TN)
data(sh_file)
# the Input Load Map by source type 1 (lines)
input_maps(catch_data_TN, annual_data_TN, sh_file, plot.type = "gr1",
legend_position = 2)
# the Input Load Map by source type 2 (lines & area)
input_maps(catch_data_TN, annual_data_TN, sh_file, plot.type = "gr2",
legend_position = 2)
```

input_plot

Plot input load by source

Description

A grouped barplot representing the average input load by source for the whole basin or a three density plots showing the distribution of nutrient sources (7 for nitrogen, 5 for phosphorous).

Usage

```
input_plot(annual_data, sh_file, basin_name, plot.type, coef_SD = 1)
```

Arguments

| | |
|-------------|---|
| annual_data | data frame. Sources of nutrient for each year and catchments. |
| sh_file | sf object. The spatial information. |
| basin_name | character. The title of the plot. |
| plot.type | character. Possible values: Bar plot ("B") or Density plot ("D"). |
| coef_SD | numeric. The standard deviation coefficient. |

Value

No return value, called for the side effect of drawing a plot

Examples

```
# the data of the TN scenario
data(annual_data_TN)
data(sh_file)
# The name of the basin
basin_name <- "Lay"
# the barplot
input_plot(annual_data = annual_data_TN, basin_name = basin_name, plot.type = "B")
# the density plots
input_plot(annual_data_TN, sh_file, basin_name, "D")
```

input_Tserie

Time series of annual load inputs by source

Description

Creates a time series plot showing basin inputs by source

Usage

```
input_Tserie(catch_data, annual_data, sh_file, basin_name, plot.type)
```

Arguments

| | |
|-------------|---|
| catch_data | data frame. Definition of the topological sequence of catchments. |
| annual_data | data frame. Sources of nutrient for each year and catchments. |
| sh_file | sf object. The spatial information. |
| basin_name | character. The title of the plot |
| plot.type | character. Alternative of the plot: "gr1": stacked area; "gr2": lines & area. |

Value

A time-series plot

Examples

```
# the data of the TN scenario
data(catch_data_TN)
data(annual_data_TN)
data(sh_file)
# The title of the plot
plotTitle <- "Time series for the Lay Basin"
# the time serie plot 1 (lines)
input_Tserie(catch_data_TN, annual_data_TN, sh_file, plotTitle, "gr1")
# the time serie plot 2 (lines & area)
input_Tserie(catch_data_TN, annual_data_TN, sh_file, plotTitle, "gr2")
```

| | |
|-------------------|--|
| input_Tserie_area | <i>Time series of annual load inputs by source and km2</i> |
|-------------------|--|

Description

Creates a time series plot showing basin inputs by source

Usage

```
input_Tserie_area(catch_data, annual_data, sh_file, basin_name, plot.type)
```

Arguments

| | |
|-------------|---|
| catch_data | data frame. Definition of the topological sequence of catchments. |
| annual_data | data frame. Sources of nutrient for each year and catchments. |
| sh_file | sf object. The spatial information. |
| basin_name | character. The title of the plot |
| plot.type | character. Alternative of the plot: "gr1": stacked area by km2; "gr2" lines & area by km2 and Shreve. |

Value

A time-series plot

Examples

```
# the data of the TN scenario
data(catch_data_TN)
data(annual_data_TN)
data(sh_file)
# The title of the plot
plotTitle <- "Time series for the Lay Basin"
# the time serie plot 1 (by km2)
```

```
input_Tserie(catch_data_TN, annual_data_TN, sh_file, plotTitle, "gr1")
# the time serie plot 2 (by km2 and Shreve)
input_Tserie(catch_data_TN, annual_data_TN, sh_file, plotTitle, "gr2")

# catch_data <- The_Scen[[1]]
# annual_data <- The_Scen[[2]]
# sh_file <- The_Sf_shape
```

LakeRetent_plot

Lake retention values summary

Description

Summary of the reference values in the stations

Usage

```
LakeRetent_plot(catch_data_TN)
```

Arguments

catch_data_TN data frame. Sources of nutrient for each year and catchments.

Value

barplot & histogram-density

Examples

```
# the data of the TN scenario
data(catch_data_TN)
LakeRetent_plot(catch_data_TN)
```

N4_sankey

Nutrient balance flow plot

Description

Nutrient balance flow in Sankey plot

Usage

```
N4_sankey(Nbalance_out)
```

Arguments

`Nbalance_out` data frame. Nutrient balance result from the `Nutbalance()` function

Value

A Sankey diagram and a data frame with the some variable values

Examples

```
# the data of the TN scenario
data(catch_data_TN)
data(annual_data_TN)
# the parameter to assess the basin model
alpha_p <- 35.09
alpha_l <- 0.02
sd_coef <- 0.2
# years in which the model should be executed
loc_years <- 1990:2018
# Computing the nutrient balance
nut_bal <- region_nut_balance(catch_data_TN, annual_data_TN, alpha_p, alpha_l,
sd_coef, loc_years)
# Plot the sankey plot with the result of the balance
sank <- N4_sankey(nut_bal)
```

nutrient_maps

Map average load output by source

Description

Creates maps showing basin output total or by source loads

Usage

```
nutrient_maps(green_file, sh_file, plot.type, style, legend_position = 1)
```

Arguments

`green_file` data frame of GREEN model results from `green_shares()` function. Nutrient Load by source apportionment of nutrient for each year and catchments.

`sh_file` sf object. The spatial information of the basin.

`plot.type` character. Alternatives of the map: “gr1”: output load (kt/y) by source; “gr2”: Total Load, log10 (kt/y); “gr3”: Total Load by km2 (kt/year/km2).

`style` character. The style of the plot.

`legend_position` numeric. Legend position: 1 (default): "right", "bottom"; 2: "left", "up"; 3: "right", "bottom"; 4: "right", "up".

Value

No return value, called for the side effect of drawing a plot

Examples

```
# the data of the TN scenario
data(catch_data_TN)
data(annual_data_TN)
data(sh_file)
# the parameter to assess the basin model
alpha_p <- 35.09
alpha_l <- 0.02
sd_coef <- 0.2
# years in which the model should be executed
loc_years <- 1990:2018
# Computing the source apportionment
basin_sa <- green_shares(catch_data_TN, annual_data_TN, alpha_p, alpha_l,
sd_coef, loc_years)
# Basin Output Load Maps by source
Lpos <- 1
nutrient_maps(basin_sa, sh_file, plot.type = "gr1", style = "log10", legend_position = Lpos)
# Basin Output Specific Load Maps
Lpos <- 1
nutrient_maps(basin_sa, sh_file, plot.type = "gr2", style = "log10", legend_position = Lpos)
# Basin Output Specific Load by km2 Maps
Lpos <- 1
nutrient_maps(basin_sa, sh_file, plot.type = "gr3", style = "fisher", legend_position = Lpos)
```

nutrient_tserie

Output load time series plot

Description

Creates a time series plot showing basin model results

Usage

```
nutrient_tserie(green_file, basin_name, plot.type, file_path = NULL)
```

Arguments

| | |
|------------|--|
| green_file | data frame. Nutrient Load by source apportionment of nutrient for each year and catchments. |
| basin_name | character. The title of the plot. |
| plot.type | character. Alternative of the plot: output load (t) by source; gr1: Basin average by Shreve (t/y/km2); gr2: Outlet total (kt/y). |
| file_path | character. The path to save the csv. |

Value

No return value, called for the side effect of drawing a plot

Examples

```
# the data of the TN scenario
data(catch_data_TN)
data(annual_data_TN)
data(sh_file)
# the parameter to assess the basin model
alpha_p <- 35.09
alpha_l <- 0.02
sd_coef <- 0.2
# years in which the model should be executed
loc_years <- 1990:2018
# Computing the source apportionment
basin_sa <- green_shares(catch_data_TN, annual_data_TN, alpha_p, alpha_l,
sd_coef, loc_years)
# The title of the plot
plotTitle <- "Time series Load Output for the Lay Basin"
# Output Load Basin average time series (lines)
nutrient_tserie(basin_sa, basin_name = plotTitle, plot.type = "gr1")
# Total Load in the Basin Outlet time series (lines)
nutrient_tserie(basin_sa, basin_name = plotTitle, plot.type = "gr2")
```

`nutrient_tserie_darea` *Output load time series plot*

Description

Creates a time series plot showing basin model results

Usage

```
nutrient_tserie_darea(green_file, sh_file, basin_name)
```

Arguments

| | |
|-------------------------|---|
| <code>green_file</code> | data frame. Nutrient Load by source apportionment of nutrient for each year and catchments. |
| <code>sh_file</code> | sf object. The spatial information. |
| <code>basin_name</code> | character. The title of the plot. |

Value

No return value, called for the side effect of drawing a plot

Examples

```
# the data of the TN scenario
data(catch_data_TN)
data(annual_data_TN)
data(sh_file)
# the parameter to assess the basin model
alpha_p <- 35.09
alpha_l <- 0.02
sd_coef <- 0.2
# years in which the model should be executed
loc_years <- 1990:2018
# Computing the source apportionment
basin_sa <- green_shares(catch_data_TN, annual_data_TN, alpha_p, alpha_l,
sd_coef, loc_years)
basin_name <- "Visla Basin"
nutrient_tserie_darea(basin_sa, sh_file, basin_name)
```

read_geometry

Read geometry

Description

Function to read the geometry file.

Usage

```
read_geometry(file)
```

Arguments

file string. A string with the name and extension of the geometry file.

Value

One object, a sf file.

| | |
|-------------|---------------------|
| read_NSdata | <i>Read NS data</i> |
|-------------|---------------------|

Description

Function to read the data and return the data frame for GREEN execution.

Usage

```
read_NSdata(path, tsn, obs, ff, rain, topo, lr, length)
```

Arguments

| | |
|--------|---|
| path | string. A string with the path of the CSV files. |
| tsn | file. A CSV file with nine variables YearValue (integer), HydroID (integer), Atm (float), Min (float), Man (float), Fix (float), Soil (float), Sd (float) and Ps (float). |
| obs | file. A CSV file with three variables YearValue (integer), HydroID (integer) and YearlyMass (float). |
| ff | file. A CSV file with three variables YearValue (integer), HydroID (integer) and ForestFraction (float). |
| rain | file. A CSV file with three variables YearValue (integer), HydroID (integer) and Rain (float). |
| topo | file. A CSV file with two variables HydroID (integer) and Next_HydroID (integer). |
| lr | file. A CSV file with three variables HydroID (integer), AvgDepth (float) and ResTime (float). |
| length | file. A CSV file with two variables HydroID (integer) and LengthKm (float). |

Value

One object, a list with two data frame. First position of the list contains the catch data and the second one the annual data.

Examples

```
path <- "https://raw.githubusercontent.com/califarog/GREENr_data/main/data/csv/"
ns_data <- read_NSdata(path, "TS_nutrients.csv", "Obs_monitoring.csv",
"ForestFr.csv", "Precipitation.csv", "Topology.csv", "LakeProperties.csv",
"Length.csv")
```

| | |
|-----------------|-------------------------------|
| references_plot | <i>Reference summary plot</i> |
|-----------------|-------------------------------|

Description

Summary of the reference values in the stations

Usage

```
references_plot(annual_data)
```

Arguments

annual_data data frame. Sources of nutrient for each year and catchments.

Value

A barplot, a histogram-density and a boxplot

Examples

```
# the data of the TN scenario
data(annual_data_TN)
references_plot(annual_data_TN)
```

| | |
|--------------------|---|
| region_nut_balance | <i>Nutrient balance based in the application of the Geospatial Regression Equation returning the diffuse, land retention, point sources</i> |
|--------------------|---|

Description

Computes the basin nutrient balance.

Usage

```
region_nut_balance(  
  catch_data,  
  annual_data,  
  alpha_p,  
  alpha_l,  
  sd_coef,  
  loc_years,  
  atm_coeff = 0.38  
)
```

Arguments

| | |
|-------------|---|
| catch_data | data frame. Definition of the topological sequence of catchments. |
| annual_data | data frame. Sources of nutrient for each year and catchments. |
| alpha_p | numeric. First model parameter, the basin retention coefficient. |
| alpha_l | numeric. Second model parameter, the river retention coefficient. |
| sd_coef | numeric. Third model parameter, fraction of domestic diffuse sources that reaches the stream network. |
| loc_years | integer. Years in which the model should be executed. |
| atm_coef | numeric. A value for atmospheric attenuation coefficient. |

Value

One object, a data frame with the basin nutrient balance

Examples

```
# the data of the TN scenario
data(catch_data_TN)
data(annual_data_TN)
# the parameter to assess the basin model
alpha_p <- 35.09
alpha_l <- 0.02
sd_coef <- 0.2
# year in which the model should be executed
loc_years <- 1990:2018
# Computing the nutrient balance
basin_loads_b <- region_nut_balance(catch_data_TN, annual_data_TN, alpha_p, alpha_l,
sd_coef, loc_years)
```

scatter_plot

Scatter plot of goodness-of-fit metric vs parameters

Description

Scatter plot of goodness-of-fit metric vs parameters

Usage

```
scatter_plot(df_cb, param)
```

Arguments

| | |
|-------|--|
| df_cb | data frame. A table with the result of the calibration process. |
| param | character. Goodness of fit metric: "NSE", "rNSE", "NSE", "mNSE", "MAE", "PBIAS", "cp", "R2", ... |

Value

Multiple scatter plot

Examples

```
# the data of the TN scenario
data(catch_data_TN)
data(annual_data_TN)
# the parameter for the calibration of the model
n_iter <- 2 # number of iterations
# the lower limits for all params (alpha_P, alpha_L, sd_coef)
low <- c(10, 0.000, 0.1)
# the upper limits for all params (alpha_P, alpha_L, sd_coef)
upp <- c(70, 0.3, 0.9)
# years in which the model should be executed
years <- 1990:2018
# execution of the calibration
df_calib <- calib_green(catch_data_TN, annual_data_TN, n_iter, low, upp,
years)
gof_mes <- "NSE"
scatter_plot(df_calib, gof_mes)
```

select_params

Selection of best calibration parameters

Description

Return the best calibration parameter set according to one goodness-of-fit metric

Usage

```
select_params(df_cb, param)
```

Arguments

| | |
|-------|---|
| df_cb | data frame. The result of the calibration process. |
| param | numeric. Goodness-of-fit measures. "NSE", "rNSE", "NSE", "mNSE", "MAE", "PBIAS", "cp", "R2",... |

Value

A vector with the 3 parameters

Examples

```
# the data of the TN scenario
data(catch_data_TN)
data(annual_data_TN)
# the parameter for the calibration of the model
n_iter <- 2 # number of iterations
# the lower limits for all params (alpha_P, alpha_L, sd_coef)
low <- c(10, 0.000, 0.1)
# the upper limits for all params (alpha_P, alpha_L, sd_coef)
upp <- c(70, 0.3, 0.9)
# years in which the model should be executed
years <- 1990:2018
# execution of the calibration
df_calib <- calib_green(catch_data_TN, annual_data_TN, n_iter, low, upp,
years)
# Extract the best set of parameter according to a Goodnes of fit metric
gof_mes <- "NSE"
NSE_bestParams <- select_params(df_calib, gof_mes)
```

shreve

Shreve

Description

Function to read the data and return the data frame for GREEN execution.

Usage

```
shreve(the_SC)
```

Arguments

the_SC table. A table with topology data.

Value

One object, a data frame with the shreve.

simobs_annual_plot *Facet year plot*

Description

This function executes a parallelized hydrological simulation and generates a comparison plot of simulated vs. observed loads. The function leverages multiple CPU cores to run the launch_green model across several years, aggregates the results, and produces a faceted scatter plot with a 1:1 reference line to evaluate model performance by year.

Usage

```
simobs_annual_plot(  
  catch_data,  
  annual_data,  
  alpha_p,  
  alpha_l,  
  sd_coef,  
  years,  
  name_basin,  
  maxvalue  
)
```

Arguments

| | |
|-------------|---|
| catch_data | data frame. Definition of the topological sequence of catchments. |
| annual_data | data frame. Sources of nutrient for each year and catchments. |
| alpha_p | numeric. First model parameter, the basin retention coefficient. |
| alpha_l | numeric. Second model parameter, the river retention coefficient. |
| sd_coef | numeric. Third model parameter, fraction of domestic diffuse sources that reaches the stream network. |
| years | integer. Years to be used in the calibration. For sequences use c(yearini:yearend). |
| name_basin | character. The name of the basin |
| maxvalue | numeric. The maximum value |

Value

One object, a data frame

Index

* datasets

- annual_data_TN, [2](#)
- annual_data_TP, [3](#)
- catch_data_TN, [7](#)
- catch_data_TP, [7](#)

- annual_data_TN, [2](#)
- annual_data_TP, [3](#)

- calib_boxplot, [4](#)
- calib_dot, [5](#)
- calib_green, [6](#)
- catch_data_TN, [7](#)
- catch_data_TP, [7](#)
- compare_calib, [8](#)

- green_shares, [9](#)

- input_maps, [10](#)
- input_plot, [11](#)
- input_Tserie, [12](#)
- input_Tserie_area, [13](#)

- LakeRetent_plot, [14](#)

- N4_sankey, [14](#)
- nutrient_maps, [15](#)
- nutrient_tserie, [16](#)
- nutrient_tserie_darea, [17](#)

- read_geometry, [18](#)
- read_NSdata, [19](#)
- references_plot, [20](#)
- region_nut_balance, [20](#)

- scatter_plot, [21](#)
- select_params, [22](#)
- shreve, [23](#)
- simobs_annual_plot, [24](#)