

# Package ‘INetTool’

March 20, 2026

**Title** Integration Network

**Version** 0.1.2

**Maintainer** Valeria Policastro <valeria.policastro@gmail.com>

**Description** It constructs a Consensus Network which identifies the general information of all the layers and Specific Networks for each layer with the information present only in that layer and not in all the others. The method is described in Policastro et al. (2024) ``INet for network integration" <doi:10.1007/s00180-024-01536-8>.

**License** MIT + file LICENSE

**Encoding** UTF-8

**RoxygenNote** 7.3.2

**Depends** R (>= 3.5.0)

**Imports** igraph, r2r, ggplot2, parallel, ggpubr, multinet, robin

**VignetteBuilder** knitr

**Suggests** knitr, rmarkdown

**LazyData** true

**NeedsCompilation** no

**Author** Valeria Policastro [aut, cre] (ORCID:  
<<https://orcid.org/0000-0003-1016-460X>>),  
Matteo Magnani [aut],  
Claudia Angelini [aut],  
Annamaria Carissimo [aut]

**Repository** CRAN

**Date/Publication** 2026-03-20 00:20:09 UTC

## Contents

|                             |   |
|-----------------------------|---|
| adjL_data . . . . .         | 2 |
| adj_rename . . . . .        | 2 |
| consensusNet . . . . .      | 3 |
| constructionGraph . . . . . | 4 |
| densityNet . . . . .        | 4 |

|                         |    |
|-------------------------|----|
| exampleL_data . . . . . | 5  |
| graphL_data . . . . .   | 5  |
| JWmatrix . . . . .      | 6  |
| JWmean . . . . .        | 6  |
| measuresNet . . . . .   | 7  |
| plotC . . . . .         | 8  |
| plotNet . . . . .       | 8  |
| plotL . . . . .         | 9  |
| specificNet . . . . .   | 10 |
| thresholdNet . . . . .  | 10 |
| tryL_data . . . . .     | 11 |

|              |           |
|--------------|-----------|
| <b>Index</b> | <b>12</b> |
|--------------|-----------|

---

|           |                       |
|-----------|-----------------------|
| adjL_data | <i>Adjacency Data</i> |
|-----------|-----------------------|

---

### Description

List of 2 adjacency matrices data type.

### Usage

```
adjL_data
```

### Format

```
## 'adjL_data' A list of 2 objects:
```

```
AdjMatrix1 Adjacency matrix;
```

```
AdjMatrix2 Adjacency matrix.
```

---

|            |                   |
|------------|-------------------|
| adj_rename | <i>adj_rename</i> |
|------------|-------------------|

---

### Description

This function constructs a list of adjacency matrices with the same row and column names for all the matrices. The output is the object needed for [consensusNet](#) function.

### Usage

```
adj_rename(adjL)
```

### Arguments

|      |                            |
|------|----------------------------|
| adjL | list of adjacency matrices |
|------|----------------------------|

**Value**

a list of adjacency matrices with the same rows and columns name.

**Examples**

```
data("tryL_data")
adj_rename(tryL_data)
```

---

|              |                     |
|--------------|---------------------|
| consensusNet | <i>consensusNet</i> |
|--------------|---------------------|

---

**Description**

This function computes the INet Algorithm for the construction of a **Consensus Network**.

**Usage**

```
consensusNet(
  adjL,
  threshold = 0.5,
  tolerance = 0.1,
  theta = 0.04,
  nitermax = 50,
  ncores = 2,
  verbose = TRUE
)
```

**Arguments**

|           |   |
|-----------|---|
| adjL      | list of weighted adjacency matrix with weights in [0,1]. Same name in rows and columns for all the matrices.    |
| threshold | threshold for the construction of the Consensus (default 0.5). Used in the last step on the similar graphs.     |
| tolerance | the tolerance of differences between similar graphs for the construction of the Consensus (default 0.1).        |
| theta     | importance to give to the neighbourhood part of the weight (default 0.04).                                      |
| nitermax  | maximum number of iteration before stopping the algorithm (default 50).   |
| ncores    | number of CPU cores to use (default is 2). We suggest to use ncores equal to the number of graphs to integrate. |
| verbose   | flag for verbose output (default as TRUE).  |

**Value**

a list of 3 types: `$graphConsensus` the Consensus Network, `$Comparison` the Jaccard weighted distances between the graphs calculated in each iteration, `$similarGraphs` the similar graphs before the Thresholding

**Examples**

```
data("adjL_data")
consensusNet(adjL_data)
```

---

constructionGraph      *constructionGraph*

---

**Description**

This function constructs graphs from data with pearson correlation and proportional thresholding (the data should be with the same names (the nodes) in columns for all the matrices).

**Usage**

```
constructionGraph(data, perc = 0.95)
```

**Arguments**

|      |   |
|------|---|
| data | a list of datasets  |
| perc | percentile (default 0.95 it takes the 5 percent of the highest weights) |

**Value**

Threshold information (highest weight, number of edges, number of nodes, modularity with louvain method), graphs in a list for each layer and weighted adjacency matrices in a list for each layer.

**Examples**

```
data("exampleL_data")
constructionGraph(exampleL_data)
```

---

densityNet      *densityNet*

---

**Description**

This function creates a density plot of the different graphs mean weights. It can be used to search the final Threshold for the Consensus Network starting from similar networks.

**Usage**

```
densityNet(graphL)
```

**Arguments**

|        |   |
|--------|---|
| graphL | the list of weighted graphs in igraph format. |
|--------|---|

**Value**

the quantile of the mean density distribution, the quantile of the mean density distribution without the zeros, plot density distribution without the zeros

**Examples**

```
data("graphL_data")
densityNet(graphL_data)
```

---

|               |                     |
|---------------|---------------------|
| exampleL_data | <i>Example Data</i> |
|---------------|---------------------|

---

**Description**

3 data types: Gene\_Expression, Methy\_Expression and Mirna\_Expression data from patients with Glioblastoma

**Usage**

```
exampleL_data
```

**Format**

```
## 'exampleL_data' A list of 3 objects:
```

**Gene\_Expression** subset of Gene expression data;

**Methy\_Expression** subset of Methylation data;

**Mirna\_Expression** subset of Mirna data.

**Source**

```
<https://portal.gdc.cancer.gov/>
```

---

|             |                   |
|-------------|-------------------|
| graphL_data | <i>Graph Data</i> |
|-------------|-------------------|

---

**Description**

List of 2 graphs of igraph class type.

**Usage**

```
graphL_data
```

**Format**

```
## 'graphL_data' A list of 2 objects:
```

**Graph1** Graph first layer;

**Graph2** Graph second layer.

---

JWmatrix

*JWmatrix*

---

**Description**

This function computes the Jaccard weighted matrix distance between all the pairs of graphs.

**Usage**

```
JWmatrix(graphL)
```

**Arguments**

graphL            list of graphs as igraph objects with the same nodes.

**Value**

weighted Jaccard distance matrix

**Examples**

```
data("graphL_data")
JWmatrix(graphL_data)
```

---

JWmean

*JWmean*

---

**Description**

This function computes the Mean Weighted Jaccard Distance for Multilayer Networks.

**Usage**

```
JWmean(graphL)
```

**Arguments**

graphL            list of different graphs in igraph format with same nodes.

**Value**

a number: the mean distance

**Examples**

```
data("graphL_data")
JWmean(graphL_data)
```

---

measuresNet

*measuresNet*

---

**Description**

This function computes graphs and nodes measures to analyse all the layers in one shot.

**Usage**

```
measuresNet(graphL, nodes.measures = TRUE)
```

**Arguments**

**graphL** a list of graphs as igraphs objects.

**nodes.measures** logical, if falso it computes only graph measures, if true it computes also nodes measures (default TRUE).

**Value**

list of measure for each layer.

**Examples**

```
data("graphL_data")
measuresNet(graphL_data)
```

plotC

*plotC*

---

**Description**

The function plots the network without isolated nodes.

**Usage**

```
plotC(graph, ...)
```

**Arguments**

|       |                 |
|-------|-----------------|
| graph | a graph         |
| ...   | other parameter |

**Value**

plot

**Examples**

```
data("graphL_data")  
plotC(graphL_data[[1]])
```

---

plotINet

*plotINet*

---

**Description**

The function plots a beginning network and the consensus in one graph with different edge colors: red edges represent edges of the consensus already present in the beginning one, while light blue edges represent new edges constructed by the consensus procedure.

**Usage**

```
plotINet(  
  adj,  
  graph.consensus,  
  edge.width = 3,  
  vertex.label.cex = 0.5,  
  vertex.size = 10,  
  edge.curved = 0.2,  
  method = "NA",  
  ...  
)
```

**Arguments**

|                  |  |
|------------------|--|
| adj              | one of the beginning adjacency matrices  |
| graph.consensus  | consensus network, output of the <code>consensusNet</code> function  |
| edge.width       | the edge width (default 3)   |
| vertex.label.cex | the size of the vertex label (default 0.8)   |
| vertex.size      | the size of the vertex (default 10)  |
| edge.curved      | to make the edge curved (default 0.2)  |
| method           | community detection method to color the nodes one of "walktrap", "edgeBetweenness", "fastGreedy", "louvain", "spinglass", "leadingEigen", "labelProp", "infomap", "optimal" and "leiden" (default no method) |
| ...              | other parameter  |

**Value**

Union graph with beginning and consensus edge. Red edges represent edges of the consensus already present in the beginning one, while light blue edges represent new edges constructed by the consensus procedure. Community detection of the beginning graph if added.

**Examples**

```
data("adjL_data")
con <- consensusNet(adjL_data)
plotINet(adjL_data[[1]], con$graphConsensus)
```

---

plotL

*plotL*


---

**Description**

This function plots all the layers in one plot(wrapper of `plot.multinet`).

**Usage**

```
plotL(graphL, ...)
```

**Arguments**

|        |                 |
|--------|-----------------|
| graphL | List of graphs  |
| ...    | other parameter |

**Value**

plot of graphs

**Examples**

```
data("graphL_data")
plotL(graphL_data)
```

---

|             |                    |
|-------------|--------------------|
| specificNet | <i>specificNet</i> |
|-------------|--------------------|

---

**Description**

The function creates Case Specific Networks one for each layer to give information of the peculiar layer not present in the Consensus.

**Usage**

```
specificNet(graphL, graph.consensus)
```

**Arguments**

graphL            a list of graphs as igraphs objects.  
graph.consensus       graphConsensus output of the [consensusNet](#) function.

**Value**

Case Specific Networks one for each layer and percentage of specificity.

**Examples**

```
data("graphL_data")
data("adjL_data")
myConsensus <- consensusNet(adjL_data)
specificNet(graphL_data, myConsensus$graphConsensus)
```

---

|              |                     |
|--------------|---------------------|
| thresholdNet | <i>thresholdNet</i> |
|--------------|---------------------|

---

**Description**

The function reconstructs the Consensus Network with different thresholding after the [consensusNet](#) function starting from similar graphs.

**Usage**

```
thresholdNet(sim.graphL, threshold = 0.5)
```

**Arguments**

`sim.graphL` a list of similarGraphs output of the `consensusNet` function.  
`threshold` different threshold to compute.

**Value**

a new consensus network igraph object.

**Examples**

```
data("adjL_data")
myConsensus <- consensusNet(adjL_data)
thresholdNet(myConsensus$similarGraphs)
```

---

`tryL_data`*try Data*

---

**Description**

Random data with different nodes name in a list of 2 adjacency matrices.

**Usage**

```
tryL_data
```

**Format**

```
## 'tryL_data' A list of 2 objects:
```

**AdjMatrix1** Adjacency matrix;

**AdjMatrix2** Adjacency matrix.

# Index

## \* datasets

- adjL\_data, [2](#)
- exampleL\_data, [5](#)
- graphL\_data, [5](#)
- tryL\_data, [11](#)

adj\_rename, [2](#)  
adjL\_data, [2](#)

consensusNet, [2, 3, 9–11](#)  
constructionGraph, [4](#)

densityNet, [4](#)

exampleL\_data, [5](#)

graphL\_data, [5](#)

JWmatrix, [6](#)  
JWmean, [6](#)

measuresNet, [7](#)

plotC, [8](#)  
plotINet, [8](#)  
plotL, [9](#)

specificNet, [10](#)

thresholdNet, [10](#)  
tryL\_data, [11](#)