

Package ‘c2z’

July 22, 2025

Type Package

Title A Reference Manager

Version 0.2.0

Maintainer Øystein Olav Skaar <oeysan@gmail.com>

Description 'Cristin' to 'Zotero' ('c2z') aims at obtaining total dominion over 'Cristin' ('Current Research Information SysTem in Norway') and 'Zotero'. The package enables manipulating 'Zotero' libraries using 'R'. Import references from 'Cristin', 'Regjeringen', 'CRAN', 'ISBN' ('Alma', 'LoC'), and 'DOI' ('CrossRef', 'DataCite') to a 'Zotero' library. Add, edit, copy, or delete items, including attachments and collections, and export references to 'BibLaTeX' (and other formats).

License MIT + file LICENSE

URL <https://github.com/oeysan/c2z/>, <https://oeysan.github.io/c2z/>

BugReports <https://github.com/oeysan/c2z/issues/>

Depends R (>= 4.1)

Imports dplyr, httr, jsonlite, purrr, rlang, rvest, stats, tibble, tidy, tidyselect, utils

Suggests covr, knitr, readr, rmarkdown, testthat (>= 3.0.0)

VignetteBuilder knitr

Config/testthat/edition 3

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

NeedsCompilation no

Author Øystein Olav Skaar [aut, cre, cph] (ORCID:
<<https://orcid.org/0000-0001-5605-3492>>)

Repository CRAN

Date/Publication 2023-08-10 07:30:05 UTC

Contents

Cristin	2
CristinMonthly	6
CristinSupported	8
CristinUnits	9
CristinWrangler	10
DoiCrossref	11
DoiDatacite	12
Zotero	13
ZoteroAdd	17
ZoteroCheck	18
ZoteroCopy	19
ZoteroCran	21
ZoteroDelete	22
ZoteroDoi	24
ZoteroExport	25
ZoteroGet	26
ZoteroGov	28
ZoteroIndex	29
ZoteroIsbn	30
ZoteroKey	31
ZoteroLibrary	32
ZoteroMatch	34
ZoteroPost	35
ZoteroTypes	37

Index	39
--------------	-----------

Cristin	<i>Search Cristin API</i>
---------	---------------------------

Description

Use search parameters for the Cristin API and return the results as a tibble. See [CristinWrangler](#)

Usage

```
Cristin(
  id = NULL,
  doi = NULL,
  title = NULL,
  contributor = NULL,
  issn = NULL,
  unit = NULL,
  institution = NULL,
  user = NULL,
  category = NULL,
```

```

published_since = NULL,
published_before = NULL,
created_since = NULL,
created_before = NULL,
modified_since = NULL,
modified_before = NULL,
year_reported = NULL,
project_code = NULL,
funding_source = NULL,
funding = NULL,
lang = NULL,
page = 1,
per_page = 1000,
max.results = NULL,
no.results = FALSE,
sort = NULL,
filter = NULL,
fields = "all",
open.query = NULL,
all.results = TRUE,
force = FALSE,
remove.duplicates = TRUE,
silent = FALSE,
base.url = "https://api.cristin.no/v2/results",
custom.url = NULL,
use.identifiers = TRUE,
crossref.search = FALSE,
autosearch = TRUE,
zotero = NULL,
zotero.import = TRUE,
zotero.check = TRUE,
remove.na = TRUE,
replace.na = "book",
force.type = NULL,
override = FALSE,
polite = TRUE,
log = list()
)

```

Arguments

id	The Cristin id of the result, Default: NULL
doi	DOI name (e.g. doi=10.1000/123456), Default: NULL
title	The title of the result, Default: NULL
contributor	Author's name or Cristin person id, Default: NULL
issn	The issn of the result, Default: NULL
unit	Id (e.g. unit=185.53.18.10), Default: NULL

<code>institution</code>	Id (one number, e.g. <code>institution=185</code>), name or acronym of the institution the contributors belong to, Default: NULL
<code>user</code>	A person's username in Cristin together with the institution id separated by colon (e.g., <code>'askeladd:185'</code>), Default: NULL
<code>category</code>	Categories. See category codes , Default: NULL
<code>published_since</code>	Results published since and inclusive the given year, (yyyy), Default: NULL
<code>published_before</code>	Results published before and inclusive the given year, (yyyy), Default: NULL
<code>created_since</code>	Results created since and inclusive the given date, (yyyy-mm-dd), Default: NULL
<code>created_before</code>	Results created before and inclusive the given date, (yyyy-mm-dd), Default: NULL
<code>modified_since</code>	Results modified since and inclusive the given date, (yyyy-mm-dd), Default: NULL
<code>modified_before</code>	Results modified before and inclusive the given date, (yyyy-mm-dd), Default: NULL
<code>year_reported</code>	The year a result was reported, Default: NULL
<code>project_code</code>	Project code is the internal reference number used by funding source, Default: NULL
<code>funding_source</code>	Funding source code e.g: NFR, Default: NULL
<code>funding</code>	Funding source code e.g: NFR, and <code>project_code</code> together separated by colon (e.g., <code>NFR:1234</code>), Default: NULL
<code>lang</code>	Two letter language code , Default: NULL
<code>page</code>	Page number. See pagination , Default: 1
<code>per_page</code>	Number of items per page (1000 is max). See pagination , Default: 1000
<code>max.results</code>	Do you need a limit?, Default: NULL
<code>no.results</code>	Do you need only the number of results?, Default: FALSE
<code>sort</code>	Sorts on 'category' and/or 'year_published'. See search and sort . Default sort order is on 'cristin_result_id' in ascending order, Default: NULL
<code>filter</code>	Vector of categories to include in results. See category code , Default: NULL
<code>fields</code>	'fields = all' gives a list of result objects with all available fields. If this parameter is omitted, a list of result summaries with fewer fields will be returned, Default: all
<code>open.query</code>	Define your own query terms, Default: NULL
<code>all.results</code>	Find all results in query, Default: TRUE
<code>force</code>	Force is seldom wise, but sometimes..., Default: FALSE
<code>remove.duplicates</code>	Remove duplicates if TRUE, Default: TRUE
<code>silent</code>	c2z is noisy, tell it to be quiet, Default: FALSE
<code>base.url</code>	The base url for the Cristin API, Default: <code>https://api.cristin.no/v2/results</code>

<code>custom.url</code>	Define your own Cristin API url, Default: NULL
<code>use.identifiers</code>	Use if ISBN/DOI identifiers if enabled, Default: TRUE
<code>crossref.search</code>	Query Crossref database based on title, authors, and date if enabled, Default: FALSE
<code>autosearch</code>	Results could be automatically evaluated (based on some logic) or you could inspect them manually if set to FALSE, Default: TRUE
<code>zotero</code>	A list with information on the specified Zotero library (e.g., id, API key, collections, and items), Default: NULL
<code>zotero.import</code>	Use CristinWrangler to wrangle metadata into an acceptable format for Zotero, Default: TRUE
<code>zotero.check</code>	Check for Cristin references already stored in Zotero, Default: TRUE
<code>remove.na</code>	Cristin contains many, more or less, obscure categories, and not all are (yet) supported. By default these are removed, however, if this option is set to FALSE unsupported categories are treated according to <code>replace.na</code> , Default: TRUE
<code>replace.na</code>	May the odds be in your favor and replace unsupported categories with a predefined <code>itemType</code> if <code>remove.na</code> is set to false, Default: 'book'
<code>force.type</code>	Force all items to a predefined <code>itemType</code> , Default: NULL
<code>override</code>	Put your faith in the algorithms and the identifiers (i.e., DOI/ISBN) and override what is reported in Cristin, Default: FALSE
<code>polite</code>	Please store you email in '.Renviron' to query Crossref, Default: TRUE
<code>log</code>	A list for storing log elements, Default: list()

Details

Please see # <https://oeysan.github.io/c2z/>

Value

A list with (exported) items from Cristin

See Also

[http_error](#), [GET](#), [RETRY](#) [tail](#), [head](#) [slice](#)

Examples

```
# Simple `Cristin` search by id
example <- Cristin(id = "840998")

# Print index using `ZoteroIndex`
if (any(nrow(example$results))) {
  ZoteroIndex(example$results) |>
  dplyr::select(name) |>
  print(width = 80)
}
```

CristinMonthly

Create a month-to-month bibliography of selected units

Description

Create a bibliography in a newsletter format from month-to-month From either a specified unit or a set of units (e.g., A University -> Faculties -> Departments -> Groups). The function has the ability to create HTML output designed for emails and/or webpages.

Usage

```
CristinMonthly(
  zotero,
  unit.key,
  style = "apa-single-spaced",
  locale = "nn-NO",
  start.date = Sys.Date(),
  end.date = NULL,
  use.filter = TRUE,
  filter = NULL,
  nvi = TRUE,
  user.cards = FALSE,
  use.identifiers = TRUE,
  zotero.check = FALSE,
  lang = "nn",
  post = FALSE,
  create.email = FALSE,
  create.web = FALSE,
  subject = NULL,
  header = NULL,
  footer = NULL,
  replace.style = TRUE,
  width = 700,
  silent = FALSE,
  log = list()
)
```

Arguments

zotero	What Zotero library to use
unit.key	What unit to search for
style	Citation style to use for appended bibliography and/or citations, Default: 'apa-single-spaced'
locale	Desired language format of bibliography, Default: 'nn-NO'
start.date	Results created from specified date (YYYY-MM), Default: Sys.Date()

<code>end.date</code>	Results created before specified date (YYYY-MM), Default: NULL
<code>use.filter</code>	Filter out specific items (otherwise supported by 'CristinWrangler'), Default: TRUE
<code>filter</code>	Filter out specific item types, will default to item types usually associated with NVI, Default: NULL
<code>nvi</code>	Filter out Cristin items not 1/2 in NVI, Default: TRUE
<code>user.cards</code>	Get business cards of contributors (currently INN), Default: FALSE
<code>use.identifiers</code>	Use if ISBN/DOI identifiers if enabled, Default: TRUE
<code>zotero.check</code>	Check if Cristin items exists in Zotero library , Default: FALSE
<code>lang</code>	Set Cristin language (nn, nb, en), Default: 'nn'
<code>post</code>	Post new items to specified Zotero library, Default: FALSE
<code>create.email</code>	Create HTML output for email, Default: FALSE
<code>create.web</code>	Create HTML output for web, Default: FALSE
<code>subject</code>	Add a custom subject to email, Default: NULL
<code>header</code>	Add a custom header to email, Default: NULL
<code>footer</code>	Add a custom footer to email, Default: NULL
<code>replace.style</code>	Email clients (e.g., Outlook) is poor at rendering CSS, and the default setting is to remove hanging indent, Default: TRUE
<code>width</code>	Width of email in pixels, Default: 700
<code>silent</code>	c2z is noisy, tell it to be quiet, Default: FALSE
<code>log</code>	A list for storing log elements, Default: list()

Details

Please see <https://oeysan.github.io/c2z/>

Value

A list with bibliography and information for defined units

See Also

[filter](#), [arrange](#), [mutate](#), [bind_rows](#), [bind_cols](#), [select](#), [group_by](#), [case_when](#), [context](#), [distinct](#), [pull](#), [mutate-joins](#), [join_by](#), [rename](#), [across](#), [reexports](#), [mutate_all](#) [pmap](#), [map](#) [tibble](#) [setName](#)

Examples

```
# Dummy example
newsletter <- CristinMonthly(
  Zotero(
    id = "4827927",
    api = "Rq1Am1H511KPghfCseAq1sQ1"
  ),
```

```
"209.0.0.0"
)
```

CristinSupported *Check for supported export formats from Cristin to Zotero*

Description

Used to filter Cristin categories that are not supported

Usage

```
CristinSupported(
  data = NULL,
  zotero.check = TRUE,
  zotero = NULL,
  remove.na = TRUE,
  replace.na = "book",
  force.type = NULL,
  remove.duplicates = TRUE,
  silent = FALSE,
  log = list()
)
```

Arguments

data	Zotero-type matrix, Default: NULL
zotero.check	Should the function look for duplicates?, Default: TRUE
zotero	List with Zotero information used to check for duplicates, Default: NULL
remove.na	Cristin contains many, more or less, obscure categories, and not all are (yet) supported. By default these are removed, however, if this option is set to FALSE unsupported categories are treated according to replace.na, Default: TRUE
replace.na	May the odds be in your favor and replace unsupported categories with a predefined itemType if remove.na is set to false, Default: 'book'
force.type	Force all items to a predefined itemType, Default: NULL
remove.duplicates	Remove duplicates if TRUE, Default: TRUE
silent	c2z is noisy, tell it to be quiet, Default: FALSE
log	A list for storing log elements, Default: list()

Details

Please see <https://oeysan.github.io/c2z/>

Value

Zotero supported items with unsupported categories as NA

See Also

[tibble](#)

Examples

```
# Supported Cristin items
print(CristinSupported(), n = 5)
```

CristinUnits *create a tibble with information about selected Cristin units*

Description

Create a tibble with information about (nested) units in Cristin (e.g., A University -> Faculties -> Departments -> Groups). The tibble can then be used to extract data for each unit from Cristin. Used by ‘CristinMonthly‘

Usage

```
CristinUnits(unit.key, subunits = TRUE, recursive = FALSE, lang = "en")
```

Arguments

unit.key	Unit to search for
subunits	Add subunits, Default: TRUE
recursive	Search for (nested) subunits, Default: FALSE
lang	PARAM_DESCRIPTION, Default: ‘en‘

Details

Used with ‘CristinMonthly‘ to create month-to-month bibliography of selected units

Value

A tibble containing information about selected units

See Also

[RETRY transmute](#), [bind_rows pmap](#)

Examples

```
# Find units for Inland University
CristinUnits("209.0.0.0") |>
  dplyr::select(id, path2) |>
  print(width = 80)
```

CristinWrangler

Wrangle Cristin metadata into Zotero-type format

Description

The little engine that could, at least try, to wrangle metadata from Cristin into a Zotero-type matrix. References can be augmented, or replaced with metadata gathered through ISBN or DOI identifiers, and through Crossref queries if all other fails. Or, hope the best and place your misguided faith in the ability of researchers to correctly register their own publications.

Usage

```
CristinWrangler(
  data,
  use.identifiers = TRUE,
  crossref.search = FALSE,
  autosearch = TRUE,
  override = FALSE,
  silent = FALSE,
  polite = TRUE,
  log = list()
)
```

Arguments

<code>data</code>	Tibble containing metadata from Cristin
<code>use.identifiers</code>	Use if ISBN/DOI identifiers if enabled, Default: TRUE
<code>crossref.search</code>	Query Crossref database based on title, authors, and date if enabled, Default: FALSE
<code>autosearch</code>	Results could be automatically evaluated (based on some logic) or you could inspect them manually if set to FALSE, Default: TRUE
<code>override</code>	Put your faith in the algorithms and the identifiers (i.e., DOI/ISBN) and override what is reported in Cristin, Default: FALSE
<code>silent</code>	Running silent, running deep, Default: FALSE
<code>polite</code>	Please store you email in ‘.Renviron’ to query Crossref, Default: TRUE
<code>log</code>	A list for storing log elements, Default: list()

Details

Please see <https://oeyasan.github.io/c2z/>

Value

A Zotero-type matrix (tibble)

See Also

[unnest](#), [nest filter](#), [across](#), [reexports](#), [bind](#), [mutate](#), [distinct](#) [RETRY](#) [tibble](#)

Examples

```
# Simple `Cristin` search by id with import set as FALSE
example <- Cristin(id = "840998", zotero.import = FALSE)

if (any(nrow(example$results))) {
  # Check if results i supported using `CristinSupported`
  example.supported <- CristinSupported(example$results)

  # Use `ZoteroIndex` to print `CristinWrangler`
  ZoteroIndex(CristinWrangler(example.supported$data)$results) |>
    dplyr::select(name) |>
    print(width = 80)
}
```

DoiCrossref

Wrangle CrossRef metadata into Zotero-type format

Description

Query CrossRef by DOI and fetch metadata

Usage

```
DoiCrossref(data, meta = list(), silent = TRUE, log = list())
```

Arguments

data	XML data from CrossRef containing metadata
meta	A list collecting all metadata used to create , Default: list()
silent	c2z is noisy, tell it to be quiet, Default: TRUE
log	A list for storing log elements, Default: list()

Details

Please see <https://oeyasan.github.io/c2z/>

Value

A Zotero-type matrix (tibble)

Examples

```
# `DoiCrossref` is called from `ZoteroDoi` (if item found)
example <- ZoteroDoi("10.1126/sciadv.abd1705")

# Print index using `ZoteroIndex`
if (!is.null(example$data)) {
  ZoteroIndex(example$data) |>
  dplyr::select(name) |>
  print(width = 80)

# Display catalog
example$data$libraryCatalog
}
```

DoiDatacite

Wrangle DataCite metadata into Zotero-type format

Description

Query DataCite by DOI and fetch metadata

Usage

```
DoiDatacite(data, meta = list(), silent = TRUE, log = list())
```

Arguments

data	XML data from DataCite containing metadata
meta	A list collecting all metadata used to create , Default: list()
silent	c2z is noisy, tell it to be quiet, Default: TRUE
log	A list for storing log elements, Default: list()

Details

Please see <https://oeysan.github.io/c2z/>

Value

A Zotero-type matrix (tibble)

Examples

```
# `DoiDatacite` is called from `ZoteroDoi` (if item found)
example <- ZoteroDoi("10.17605/OSF.IO/7HZ4P")

# Use `ZoteroIndex` to print
# Print index using `ZoteroIndex`
if (any(nrow(example$data))) {
  ZoteroIndex(example$data) |>
    dplyr::select(name) |>
    print(width = 80)

# Display catalog
example$data$libraryCatalog
}
```

Zotero

Connect to Zotero API

Description

Wrapper to connect with the Zotero API and the main functions of **c2z**

Usage

```
Zotero(
  collection.names = NULL,
  collection.key = NULL,
  collection.path = NULL,
  item.key = NULL,
  library = FALSE,
  case.insensitive = TRUE,
  ancestor = FALSE,
  recursive = FALSE,
  create = FALSE,
  limit = 100,
  start = 0,
  get.collections = TRUE,
  get.items = TRUE,
  item.type = NULL,
  all.results = TRUE,
  max.results = NULL,
  collections = NULL,
  items = NULL,
  attachments = NULL,
  metadata = NULL,
  doi = NULL,
  isbn = NULL,
```

```
export = FALSE,
csl.type = NULL,
csl.name = "style",
format = "biblatex",
save.data = FALSE,
save.path = NULL,
bib.name = "references",
library.type = NULL,
linkwrap = 1,
style = "apa",
locale = "en-US",
copy = FALSE,
copy.collections = TRUE,
copy.items = TRUE,
copy.extras = TRUE,
remove.missing = TRUE,
change.library = FALSE,
copy.user = TRUE,
copy.id = NULL,
copy.api = NULL,
post = FALSE,
post.collections = TRUE,
post.items = TRUE,
post.attachments = TRUE,
post.limit = 50,
delete = FALSE,
delete.collections = FALSE,
delete.items = FALSE,
delete.limit = 50,
ragnarok = FALSE,
user = TRUE,
index = FALSE,
id = NULL,
token = NULL,
token.api = NULL,
api = NULL,
force = FALSE,
base.url = "https://api.zotero.org",
silent = FALSE,
zotero = NULL,
log = list()
)
```

Arguments

`collection.names` Vector of collection names to create or search for, Default: NULL

`collection.key` A specified collection key, Default: NULL

collection.path	Vector of nested collection keys, Default: NULL
item.key	A specified item key, Default: NULL
library	Use 'ZoteroLibrary' to fetch collections and items, Default: FALSE
case.insensitive	Disregard letter casing when searching for collections, Default: TRUE
ancestor	Trace the lineage of a collection (i.e., find the top-level collection), Default: FALSE
recursive	Find all nested collections, Default: FALSE
create	Create missing collections, Default: FALSE
limit	Number of results per query (max 100), Default: 100
start	Starting position of query (0 = first result), Default: 0
get.collections	Fetch collections, Default: TRUE
get.items	Fetch items, Default: TRUE
item.type	Items to search for (NULL = everything), Default: NULL
all.results	Find all results in query, Default: TRUE
max.results	Do you need a limit?, Default: NULL
collections	Predefined collections (as tibble), Default: NULL
items	Predefined metadata (as tibble), Default: NULL
attachments	Predefined attachments (as tibble), Default: NULL
metadata	Predefined metadata in Zotero-format, Default: NULL
doi	Use ZoteroDoi to fetch DOI metadata, Default: NULL
isbn	Use ZoteroIsbn to fetch ISBN metadata, Default: NULL
export	Use 'ZoteroExport' to export items, Default: FALSE
cs1.type	Specify a CSL type to Official repository for Citation Style Language (CSL), Default: NULL
cs1.name	Name of saved CSL file, Default: 'style'
format	Export format of Zotero items, Default: 'bibtex'
save.data	Save data (e.g., bibliography) to disk, Default: FALSE
save.path	Location to store data on disk, Default: NULL
bib.name	Name of exported bibliography, Default: 'references'
library.type	Commma-separated data from Zotero (i.e., data, bib, citation), Default: NULL
linkwrap	Set URL (e.g., DOI) as HTML link (1 = yes), Default: 1
style	Citation style to use for appended bibliography and/or citations, Default: apa
locale	Desired language format of bibliography, Default: 'en-US'
copy	Use 'ZoteroCopy' to delete collections and/or items, Default: FALSE
copy.collections	Try to copy specified collections, Default: TRUE

copy.items	Try to copy specified items?, Default: TRUE
copy.extras	Try to copy specified extras (i.e., attachments and notes)?, Default: TRUE
remove.missing	Deleted missing extras, Default: TRUE
change.library	Stage changing of library (e.g., from a group to a personal library), Default: FALSE
copy.user	New user type (The functions will use 'group' as prefix if FALSE), Default: TRUE
copy.id	New id, Default: NULL
copy.api	New API key. Set API to 'NA' if key is not needed, Default: NULL
post	Use 'ZoteroPost' to post collections and/or items, Default: FALSE
post.collections	Try to copy specified collections, Default: TRUE
post.items	Try to copy specified items?, Default: TRUE
post.attachments	Try to copy specified extras (i.e., attachments and notes)?, Default: TRUE
post.limit	Number of collections/items to post per request (max 50), Default: 50
delete	Use 'ZoteroDelete' to delete collections and/or items, Default: FALSE
delete.collections	Try to delete specified collections, Default: TRUE
delete.items	Try to delete specified items?, Default: TRUE
delete.limit	Number of collections/items to delete per request (max 50), Default: 50
ragnarok	Delete EVERYTHING in the specified library, Default: FALSE
user	User type (The functions will use 'group' as prefix if FALSE), Default: TRUE
index	Create an index of items, Default: FALSE
id	User or group ID, Default: NULL
token	Name of user or group token as defined in '.Renviron', Default: NULL
token.api	Name of API token as defined in '.Renviron', Default: NULL
api	API key to connect with the Zotero library. Set API to 'NA' if key is not needed. See Zotero API , Default: NULL
force	Force is seldom wise, but sometimes..., Default: FALSE
base.url	Base url of the Zotero API, Default: 'https://api.zotero.org'
silent	c2z is noisy, tell it to be quiet, Default: FALSE
zotero	A list with information on the specified Zotero library (e.g., id, API key, collections, and items), Default: NULL
log	A list for storing log elements, Default: list()

Details

Please see <https://oeyasan.github.io/c2z/>

Value

A list with information on the specified Zotero library (e.g., id, API key, collections, and items)

See Also

[http_error](#), [GET](#)

Examples

```
# Create the default Zotero list
example <- Zotero(id = "9913421", api = "Rq1AmlH511KPghfCseAq1sQ1")
# Print the interesting pars of an otherwise empty list
print(tail(example,5))
```

ZoteroAdd

Add items to Zotero list

Description

Use identifiers or predefined data to add to the Zotero list

Usage

```
ZoteroAdd(zotero, metadata = NULL, doi = NULL, isbn = NULL, silent = FALSE)
```

Arguments

zotero	A list with information on the specified Zotero library (e.g., id, API key, collections, and items)
metadata	Predefined metadata in Zotero-format, Default: NULL
doi	Use ZoteroDoi to fetch DOI metadata, Default: NULL
isbn	Use ZoteroIsbn to fetch ISBN metadata, Default: NULL
silent	c2z is noisy, tell it to be quiet, Default: FALSE

Details

Please see <https://oeysan.github.io/c2z/>

Value

Will add data to the Zotero list

Examples

```
# Add items from `ZoteroIsbn` to the default Zotero list
example <- ZoteroAdd(
  Zotero(
    id = "9913421",
    api = "Rq1AmlH511KPghfCseAq1sQ1"
  ),
  isbn = "978-1529797138"
)
# Print index using `ZoteroIndex`
if (any(nrow(example$items))) {
  ZoteroIndex(example$items) |>
  dplyr::select(name) |>
  print(width = 80)
}
```

ZoteroCheck

Check Zotero library for duplicates

Description

Remove references that are not modified since last added to Zotero

Usage

```
ZoteroCheck(
  data,
  id,
  id.type,
  created,
  last.modified,
  zotero = NULL,
  remove.duplicates = TRUE,
  silent = FALSE,
  log = list()
)
```

Arguments

data	Tibble containing metadata (from Cristin)
id	column containing identifier (e.g., <code>cristin_result_id</code>)
id.type	Type of metadata as found in the Zotero extra field ("e.g., <code>Cristin</code>)
created	column containing creation date in UNIX timestamp format (e.g., <code>created</code>)
last.modified	column containing modification date in UNIX timestamp format (e.g., <code>last_modified</code>)
zotero	A list with information on the specified Zotero library (e.g., id, API key, collections, and items), Default: <code>NULL</code>

`remove.duplicates` Remove duplicates if TRUE, Default: TRUE
`silent` c2z is noisy, tell it to be quiet, Default: FALSE
`log` A list for storing log elements, Default: list()

Details

Please see <https://oeysan.github.io/c2z/>

Value

Returns non-duplicated data in a Zotero-type matrix (tibble)

See Also

[arrange](#), [coalesce](#), [bind_rows](#), [filter](#)

Examples

```
# Simple `Cristin` search by id
cristin.data <- Cristin(
  id = "840998",
  zotero.import = FALSE
)

# Simple `ZoteroCheck`
example <- ZoteroCheck(
  data = cristin.data$result,
  id = "cristin_result_id",
  id.type = "Cristin",
  created = "created",
  last.modified = "last_modified",
  zotero = Zotero(
    user = FALSE,
    id = "4827927",
    api = "Rq1AmlH511KPghfCseAq1sQ1",
    library = TRUE,
    silent = TRUE
  )
)
```

Description

Replace key identifiers with new ones while keeping existing structure and relationship between collections and items

Usage

```
ZoteroCopy(
  zotero,
  copy.collections = TRUE,
  copy.items = TRUE,
  copy.extras = TRUE,
  remove.missing = TRUE,
  change.library = FALSE,
  copy.user = TRUE,
  copy.id = NULL,
  copy.api = NULL,
  silent = FALSE
)
```

Arguments

zotero	A list with information on the specified Zotero library (e.g., id, API key, collections, and items)
copy.collections	Try to copy specified collections, Default: TRUE
copy.items	Try to copy specified items?, Default: TRUE
copy.extras	Try to copy specified extras (i.e., attachments and notes)?, Default: TRUE
remove.missing	Deleted missing extras, Default: TRUE
change.library	Stage changing of library (e.g., from a group to a personal library), Default: FALSE
copy.user	New user type (The functions will use 'group' as prefix if FALSE), Default: TRUE
copy.id	New id, Default: NULL
copy.api	New API key, Default: NULL
silent	c2z is noisy, tell it to be quiet, Default: FALSE

Details

Please see <https://oeysan.github.io/c2z/>

Value

A list with information on the specified Zotero library (e.g., copied collections and items)

See Also

[GET mutate](#), [case_when](#), [filter](#), [select](#), [across](#), [arrange](#) [pmap](#) [all_of](#)

Examples

```
# Fetching collections and items from default group
zotero = Zotero(
  user = FALSE,
  id = "4827927",
  api = "Rq1AmlH511KPghfCseAq1sQ1",
  library = TRUE
)

# Display collections
if (any(nrow(zotero$collections))) {
  zotero$collections |>
    dplyr::select(key, version, parentCollection) |>
    print(width = 80)
}

# Display items
if (any(nrow(zotero$items))) {
  zotero$items |>
    dplyr::select(key, version) |>
    print(width = 80)
}

# Copy items
example <- ZoteroCopy(
  zotero,
)

# Display collections
if (any(nrow(example$collections))) {
  example$collections |>
    dplyr::select(key, version, parentCollection) |>
    print(width = 80)
}

# Display items
if (any(nrow(example$items))) {
  example$items |>
    dplyr::select(key, version) |>
    print(width = 80)
}
```

Description

Query CRAN by name and fetch metadata

Usage

```
ZoteroCran(id, meta = list(), silent = TRUE, log = list())
```

Arguments

id	name of R package
meta	A list collecting all metadata used to create , Default: list()
silent	c2z is noisy, tell it to be quiet, Default: TRUE
log	A list for storing log elements, Default: list()

Details

Please see <https://oeysan.github.io/c2z/>

Value

A Zotero-type matrix (tibble)

See Also

[RETRY reexports](#)

Examples

```
# Search cran for package `dplyr`
example <- ZoteroCran(c("dplyr", "jsonlite", "httr"))

# Print index using `ZoteroIndex`
if (any(nrow(example$data))) {
  ZoteroIndex(example$data) |>
    dplyr::select(name) |>
    print(width = 80)
}
```

ZoteroDelete

Delete collections and items from a Zotero library

Description

Cleaning the Zotero library

Usage

```
ZoteroDelete(
  zotero,
  delete.collections = FALSE,
  delete.items = FALSE,
  delete.limit = 50,
  force = FALSE,
  ragnarok = FALSE,
  silent = FALSE
)
```

Arguments

zotero	A list with information on the specified Zotero library (e.g., id, API key, collections, and items)
delete.collections	Try to delete specified collections, Default: TRUE
delete.items	Try to delete specified items?, Default: TRUE
delete.limit	Number of collections/items to delete per request (max 50), Default: 50
force	Force is seldom wise, but sometimes..., Default: FALSE
ragnarok	Delete EVERYTHING in the specified library, Default: FALSE
silent	c2z is noisy, tell it to be quiet, Default: FALSE

Details

Please see <https://oeysan.github.io/c2z/>

Value

A list with information on the specified Zotero library (e.g., deleted collections and items)

See Also

[add_headers](#), [RETRY](#)

Examples

```
# Delete everything in a group
example <- ZoteroDelete(
  Zotero(
    user = FALSE,
    id = "4988497",
    api = "Rq1AmlH511KPghfCseAq1sQ1"
  ),
  ragnarok = TRUE,
  force = TRUE
)
```

ZoteroDoi

Use DOI to acquire metadata

Description

Connects with doi.org to create metadata

Usage

```
ZoteroDoi(doi, meta = list(), silent = TRUE, log = list())
```

Arguments

doi	A digital object identifier
meta	A list collecting all metadata used to create , Default: list()
silent	c2z is noisy, tell it to be quiet, Default: TRUE
log	A list for storing log elements, Default: list()

Details

Please see <https://oeysan.github.io/c2z/>

Value

A Zotero-type matrix (tibble)

See Also

[http_error](#), [GET](#), [RETRY](#) [rename](#), [html_attr](#), [html_text](#), [reexports](#), [html_children](#), [html_name](#), [bind](#), [arrange](#)

Examples

```
# Simple use of `ZoteroDoi`
example <- ZoteroDoi("10.1126/sciadv.abd1705")

# Print index using `ZoteroIndex`
if (any(nrow(example$data))) {
  ZoteroIndex(example$data) |>
  dplyr::select(name) |>
  print(width = 80)
}
```

ZoteroExport

Export Zotero items to bibliography

Description

Export Zotero items to a specified format (e.g., BibLaTeX) using a CSL format (e.g., APA7)

Usage

```
ZoteroExport(
  zotero,
  csl.type = NULL,
  csl.name = "style",
  locale = "en-US",
  format = "biblatex",
  bib.name = "references",
  save.data = FALSE,
  save.path = NULL,
  silent = FALSE
)
```

Arguments

zotero	A list with information on the specified Zotero library (e.g., id, API key, collections, and items)
csl.type	Specify a CSL type to Official repository for Citation Style Language (CSL), Default: NULL
csl.name	Name of saved CSL file, Default: 'style'
locale	Desired language format of bibliography, Default: 'en-US'
format	Export format of Zotero items, Default: 'biblatex'
bib.name	Name of exported bibliography, Default: 'references'
save.data	Save data (e.g., bibliography) to disk, Default: FALSE
save.path	Location to store data on disk, Default: NULL
silent	c2z is noisy, tell it to be quiet, Default: FALSE

Details

Please see <https://oeyasan.github.io/c2z/>

Value

A list with information on the specified Zotero library (e.g., exported items, bibliography and citations)

See Also[select where](#)**Examples**

```
# Define Zotero list according to default group
zotero = Zotero(
  user = FALSE,
  id = "4827927",
  api = "Rq1Am1H511KPghfCseAq1sQ1",
  item.type = "-attachment || note",
  max.result = 1,
  library = TRUE
)

# Export 1 items from the default group
example <- ZoteroExport(
  zotero
)

# Display exported
cat(example$export, fill = 80)
```

ZoteroGet*Get collections and items from a Zotero library*

Description

Get

Usage

```
ZoteroGet(
  zotero,
  use.collection = TRUE,
  use.item = FALSE,
  append.collections = FALSE,
  append.items = FALSE,
  append.top = FALSE,
  append.file = FALSE,
  custom.url = NULL,
  open.query = NULL,
  limit = 100,
  start = 0,
  format = "json",
  item.keys = NULL,
  collection.keys = NULL,
  item.type = NULL,
```

```

    library.type = NULL,
    linkwrap = 1,
    style = "apa",
    locale = "en-US",
    all.results = TRUE,
    max.results = NULL,
    result.type = NULL,
    force = FALSE,
    silent = FALSE
)

```

Arguments

zotero	A list with information on the specified Zotero library (e.g., id, API key, collections, and items)
use.collection	Use collection key if present in Zotero list, Default: TRUE
use.item	Use item key if present in Zotero list, Default: FALSE
append.collections	Append '/collections/' to Zotero API url, Default: FALSE
append.items	Append '/items/' to Zotero API url, Default: FALSE
append.top	Append '/top/' to Zotero API url, Default: FALSE
append.file	Append '/file/' to Zotero API url, Default: FALSE
custom.url	Use a custom Zotero API url, Default: NULL
open.query	Use your own query, Default: NULL
limit	Number of results per query (max 100), Default: 100
start	Starting position of query (0 = first result), Default: 0
format	Format of response from the Zotero API, Default: 'json'
item.keys	Specified vector of items keys, Default: NULL
collection.keys	Specified vector of collection keys, Default: NULL
item.type	Items to search for (NULL = everything), Default: NULL
library.type	Commma-separated data from Zotero (i.e., data, bib, citation), Default: NULL
linkwrap	Set URL (e.g., DOI) as HTML link (1 = yes), Default: 1
style	Citation style to use for appended bibliography and/or citations, Default: apa
locale	Desired language format of bibliography, Default: 'en-US'
all.results	Find all results in query, Default: TRUE
max.results	Do you need a limit?, Default: NULL
result.type	Pointless linguistics to display result type (default = 'result'), Default: NULL
force	Force is seldom wise, but sometimes..., Default: FALSE
silent	c2z is noisy, tell it to be quiet, Default: FALSE

Details

Please see <https://oeysan.github.io/c2z/>

Value

A list with information on the specified Zotero library (e.g., collections and items)

See Also

[RETRY](#)

Examples

```
# Define Zotero list according to default settings
zotero = Zotero(
  user = FALSE,
  id = "4827927",
  api = "Rq1Am1H511KPghfCseAq1sQ1"
)

# Query default group Zotero library for 1 item
example <- ZoteroGet(
  zotero,
  max.results = 1
)

# Print index using `ZoteroIndex`
if (any(nrow(example$results))) {
  ZoteroIndex(example$results) |>
  dplyr::select(name) |>
  print(width = 80)
}
```

ZoteroGov

Wrangle regjeringen.no metadata into Zotero-type format

Description

Query regjeringen by search word and type and fetch metadata

Usage

```
ZoteroGov(search, type = "NOU", meta = list(), silent = TRUE, log = list())
```

Arguments

search	Search term (e.g., 2018: 2)
type	type of query (e.g., white paper, official norwegian reports), Default: "NOU"
meta	A list collecting all metadata used to create , Default: list()
silent	c2z is noisy, tell it to be quiet, Default: TRUE
log	A list for storing log elements, Default: list()

Details

Please see <https://oeysan.github.io/c2z/>

Value

A Zotero-type matrix (tibble)

See Also

[RETRY reexports bind, arrange](#)

Examples

```
# Search the default entity, Norwegian official reports in regjeringen.no
example <- ZoteroGov("2001:4")
# Print index using `ZoteroIndex`
if (any(nrow(example$data))) {
  ZoteroIndex(example$data) |>
    dplyr::select(name) |>
    print(width = 80)
}
```

ZoteroIndex

Create an index of Zotero items

Description

The function creates a index containing key information about the present Zotero items

Usage

```
ZoteroIndex(data)
```

Arguments

data Tibble containing Zotero-type metadata (e.g., from Cristin)

Details

Please see <https://oeysan.github.io/c2z/>

Value

A tibble

See Also

[filter](#), [mutate](#), [across](#), [na_if](#), [case_when](#), [arrange](#), [group_by](#), [context](#), [select everything](#)
[pmap](#)

Examples

```
# Access the default group library
example = Zotero(
  user = FALSE,
  id = "4827927",
  api = "Rq1Am1H511KPghfCseAq1sQ1",
  library = TRUE
)
# Print index using `ZoteroIndex`
if (any(nrow(example$items))) {
  ZoteroIndex(example$items) |>
  dplyr::select(name) |>
  print(width = 80)
}
```

ZoteroIsbn

Search libraries using ISBN or MMS ID

Description

Query libraries using ISBN (or MMS ID) and fetch metadata

Usage

```
ZoteroIsbn(keys, meta = list(), silent = TRUE, log = list())
```

Arguments

keys	Keys to search with (e.g., ISBN or MMS ID)
meta	A list collecting all metadata used to create , Default: list()
silent	c2z is noisy, tell it to be quiet, Default: TRUE
log	A list for storing log elements, Default: list()

Details

Please see <https://oeysan.github.io/c2z/>

Value

A Zotero-type matrix (tibble)

See Also

[rename](#), [html_children](#), [html_attr](#), [html_text](#), [reexports bind](#), [distinct](#), [arrange tibble](#)
[RETRY setNames toJSON](#), [fromJSON](#)

Examples

```
# Search libraries for ISBN metadata
example <- ZoteroIsbn("978-1529797138")

# Print index using `ZoteroIndex`
if (any(nrow(example$data))) {
  ZoteroIndex(example$data) |>
    dplyr::select(name) |>
    print(width = 80)
}
```

ZoteroKey

Create Zotero key or write token

Description

Create an identifier for Zotero items/collections or a write token to library

Usage

```
ZoteroKey(token = FALSE)
```

Arguments

token Create a write token, Default: FALSE

Details

Please see <https://oeysan.github.io/c2z/>

Value

Will return a 8 character Zotero key or 32 character write token

Examples

```
# Create a Zotero key
key <- ZoteroKey()
# Create a write token
token <- ZoteroKey(TRUE)
```

ZoteroLibrary

Access the Zotero library

Description

The function uses information stored in the ‘zotero’ list to access specified collections and items in the Zotero library

Usage

```
ZoteroLibrary(
  zotero,
  case.insensitive = TRUE,
  ancestor = FALSE,
  recursive = FALSE,
  create = FALSE,
  limit = 100,
  start = 0,
  get.collections = TRUE,
  get.items = TRUE,
  item.type = NULL,
  all.results = TRUE,
  max.results = NULL,
  library.type = NULL,
  linkwrap = 1,
  style = "apa",
  locale = "en-US",
  force = FALSE,
  silent = FALSE
)
```

Arguments

zotero	A list with information on the specified Zotero library (e.g., id, API key, collections, and items)
case.insensitive	Disregard letter casing when searching for collections, Default: TRUE
ancestor	Trace the lineage of a collection (i.e., find the top-level collection), Default: FALSE
recursive	Find all nested collections, Default: FALSE

<code>create</code>	Create missing collections, Default: FALSE
<code>limit</code>	Number of results per query (max 100), Default: 100
<code>start</code>	Starting position of query (0 = first result), Default: 0
<code>get.collections</code>	Fetch collections, Default: TRUE
<code>get.items</code>	Fetch items, Default: TRUE
<code>item.type</code>	Items to search for (NULL = everything), Default: NULL
<code>all.results</code>	Find all results in query, Default: TRUE
<code>max.results</code>	Do you need a limit?, Default: NULL
<code>library.type</code>	Commma-separated data from Zotero (i.e., data, bib, citation), Default: NULL
<code>linkwrap</code>	Set URL (e.g., DOI) as HTML link (1 = yes), Default: 1
<code>style</code>	Citation style to use for appended bibliography and/or citations, Default: apa
<code>locale</code>	Desired language format of bibliography, Default: 'en-US'
<code>force</code>	Force is seldom wise, but sometimes..., Default: FALSE
<code>silent</code>	c2z is noisy, tell it to be quiet, Default: FALSE

Details

Please see <https://oeysan.github.io/c2z/>

Value

A list with information on the specified Zotero library (e.g., collections and items)

See Also

[toJSON](#), [fromJSON](#) [distinct](#), [arrange](#) [tibble](#)

Examples

```
# Access the default group library
example <- ZoteroLibrary(
  Zotero(
    user = FALSE,
    id = "4827927",
    api = "Rq1AmlH511KPghfCseAq1sQ1"
  )
)
# Print index using `ZoteroIndex`
if (any(nrow(example$items))) {
  ZoteroIndex(example$items) |>
  dplyr::select(name) |>
  print(width = 80)
}
```

ZoteroMatch

Search or match items using CrossRef

Description

Use the CrossRef API to match data (e.g., Cristin metadata with Crossref metadata) or search by title, authors and date

Usage

```
ZoteroMatch(
  title,
  authors,
  date,
  haystack = NULL,
  haystack.size = 3,
  crossref.search = FALSE,
  autosearch = FALSE,
  cristin.data = NULL,
  external.data = NULL,
  polite = TRUE,
  silent = FALSE,
  log = list()
)
```

Arguments

title	Title of reference
authors	creators of the reference
date	publication date of the reference
haystack	Potential matches for search term (i.e., needle), Default: NULL
haystack.size	Number of items in the haystack, Default: 3
crossref.search	Search CrossRef if needle not found in haystack, Default: FALSE
autosearch	Match automatically or compare needle with haystack, Default: FALSE
cristin.data	Metadata from Cristin, Default: NULL
external.data	Metadata from external source (e.g., CrossRef), Default: NULL
polite	Will use an email stored in '.Renviron', Default: TRUE
silent	Running silent, running deep, Default: FALSE
log	A list for storing log elements, Default: list()

Details

Please see <https://oeyasan.github.io/c2z/>

Value

A Zotero-type matrix (tibble) if match is found otherwise NULL

See Also

[select](#), [reexports](#), [mutate](#), [coalesce](#), [pull](#) [sym](#) [RETRY](#) [toJSON](#), [fromJSON](#) [adist](#), [head](#) [map](#)

Examples

```
# Conduct an autosearch in CrossRef using title, authors and date
example <- ZoteroMatch(
  title = "Nonreplicable publications",
  authors = "Serra-Garcia & Gneezy",
  date = "2021",
  autosearch = TRUE
)

# Print index using `ZoteroIndex`
if (any(nrow(example$data))) {
  ZoteroIndex(example$data) |>
  dplyr::select(name) |>
  print(width = 80)
}
```

ZoteroPost

Post collections and items to a Zotero library

Description

Create or update collections and items in a specified library

Usage

```
ZoteroPost(
  zotero,
  post.collections = TRUE,
  post.items = TRUE,
  post.attachments = TRUE,
  post.limit = 50,
  force = FALSE,
  silent = FALSE
)
```

Arguments

zotero	A list with information on the specified Zotero library (e.g., id, API key, collections, and items)
post.collections	Try to copy specified collections, Default: TRUE
post.items	Try to copy specified items?, Default: TRUE
post.attachments	Try to copy specified extras (i.e., attachments and notes)?, Default: TRUE
post.limit	Number of collections/items to post per request (max 50), Default: 50
force	Force is seldom wise, but sometimes..., Default: FALSE
silent	c2z is noisy, tell it to be quiet, Default: FALSE

Details

Please see <https://oeysan.github.io/c2z/>

Value

A list with information on the specified Zotero library (e.g., posted collections and items)

See Also

[select](#), [bind](#), [mutate](#) [add_headers](#), [RETRY toJSON](#), [fromJSON as_tibble](#), [add_column stack setNames](#)

Examples

```
# Connect to the public group "c2z_delete"
# NB! This process can be done using only `Zotero` (see README)
zotero <- Zotero(
  user = FALSE,
  id = "4988497",
  api = "Rq1Am1H511KPghfCseAq1sQ1"
)

# Create a new collection for POST
zotero$collections <- tibble::tibble(
  key = ZoteroKey(),
  version = 0,
  name = "Post-test",
  parentCollection = "FALSE"
)

# Add item to post using `ZoteroAdd` (and `ZoteroDoi`)
zotero <- ZoteroAdd(
  zotero,
  doi = "10.1126/sciadv.abd1705"
)
```

```

# Post a DOI to the public group "c2z_delete"
example <- ZoteroPost(
  zotero,
  post.collections = TRUE,
  post.items = TRUE
)

# Delete collections and items using `ZoteroDelete`
delete.example <- ZoteroDelete(
  zotero,
  delete.collections = TRUE,
  delete.items = TRUE
)

# Print index using `ZoteroIndex`
if (any(nrow(example$items))) {
  ZoteroIndex(example$items) |>
  dplyr::select(name) |>
  print(width = 80)
}

```

ZoteroTypes

List with empty zotero-items

Description

Each tibble in the list represents a zotero-item

Usage

```
ZoteroTypes(type = NULL, names = TRUE)
```

Arguments

type	Type of zotero-item, Default: NULL
names	return only column names if set to TRUE, Default: TRUE

Format

A list with 36 tibbles with zero rows and various columns

Details

Used to create Zotero-items from list of metadata

Value

Either list of zotero-items or specified item

Examples

```
# All zotero-items
names(ZoteroTypes())
# Column names of item-type `book`
ZoteroTypes("book")
```

Index

across, [7](#), [11](#), [20](#), [30](#)
add_column, [36](#)
add_headers, [23](#), [36](#)
adist, [35](#)
all_of, [20](#)
arrange, [7](#), [19](#), [20](#), [24](#), [29–31](#), [33](#)
as_tibble, [36](#)

bind, [11](#), [24](#), [29](#), [31](#), [36](#)
bind_cols, [7](#)
bind_rows, [7](#), [9](#), [19](#)

case_when, [7](#), [20](#), [30](#)
coalesce, [19](#), [35](#)
context, [7](#), [30](#)
Cristin, [2](#)
CristinMonthly, [6](#)
CristinSupported, [8](#)
CristinUnits, [9](#)
CristinWrangler, [2](#), [5](#), [10](#)

distinct, [7](#), [11](#), [31](#), [33](#)
DoiCrossref, [11](#)
DoiDatacite, [12](#)

everything, [30](#)

filter, [7](#), [11](#), [19](#), [20](#), [30](#)

GET, [5](#), [17](#), [20](#), [24](#)
group_by, [7](#), [30](#)

head, [5](#), [35](#)
html_attr, [24](#), [31](#)
html_children, [24](#), [31](#)
html_name, [24](#)
html_text, [24](#), [31](#)
http_error, [5](#), [17](#), [24](#)

join_by, [7](#)

map, [7](#), [35](#)

mutate, [7](#), [11](#), [20](#), [30](#), [35](#), [36](#)
mutate_all, [7](#)

na_if, [30](#)
nest, [11](#)

pmap, [7](#), [9](#), [20](#), [30](#)
pull, [7](#), [35](#)

reexports, [7](#), [11](#), [22](#), [24](#), [29](#), [31](#), [35](#)
rename, [7](#), [24](#), [31](#)
RETRY, [5](#), [9](#), [11](#), [22–24](#), [28](#), [29](#), [31](#), [35](#), [36](#)

select, [7](#), [20](#), [26](#), [30](#), [35](#), [36](#)
setNames, [7](#), [31](#), [36](#)
slice, [5](#)
stack, [36](#)
sym, [35](#)

tail, [5](#)
tibble, [7](#), [9](#), [11](#), [31](#), [33](#)
transmute, [9](#)

unnest, [11](#)

where, [26](#)

Zotero, [13](#)
ZoteroAdd, [17](#)
ZoteroCheck, [18](#)
ZoteroCopy, [19](#)
ZoteroCran, [21](#)
ZoteroDelete, [22](#)
ZoteroDoi, [15](#), [17](#), [24](#)
ZoteroExport, [25](#)
ZoteroGet, [26](#)
ZoteroGov, [28](#)
ZoteroIndex, [29](#)
ZoteroIsbn, [15](#), [17](#), [30](#)
ZoteroKey, [31](#)
ZoteroLibrary, [32](#)

ZoteroMatch, [34](#)
ZoteroPost, [35](#)
ZoteroTypes, [37](#)